RSC Advances



PAPER

View Article Online
View Journal | View Issue



Cite this: RSC Adv., 2017, 7, 52435

Dual mode temperature sensing through luminescence lifetimes of F- and O-coordinated Cr³⁺ sites in fluorosilicate glass-ceramics†

Changjian Wang,^a Abhishek Wadhwa,^a Shuo Cui,^{ab} Ronghua Ma,^a Xvsheng Qiao, (1)** Xianping Fan (1)** and Xianghua Zhang^b

Luminescence lifetime based temperature sensing has an intrinsic immunity to the influence of external conditions, and dual mode thermometry is highly accurate due to its "self-calibration" merit. To develop thermometry with both features, we investigated the phase and microstructural evolution of Cr³⁺-doped calcium-fluorosilicate glass and glass-ceramics, which revealed different luminescent behavior relating to the different Cr^{3+} sites in the materials. From the photoluminescence (PL) spectra, the emission at 717 nm was derived from the O-coordinated octahedral sites, while the 1 μ m super-broad emission was assigned to the F-coordinated octahedral sites. After an annealing treatment, cubic CaF2 nanocrystals were homogeneously precipitated in the glass-ceramics; thus, both the O-coordination in the residual glass phase and F-coordination in the CaF2 crystalline phase were strengthened. This led to the enhancement of both the emissions at 717 nm and 1 μm . The O-coordinated sites were relatively strong-field sites in which the fluorescence of Cr³⁺ originated from the radiative transitions of the two thermally coupled energy levels, ²E and ⁴T₂, while the F-coordinated sites were relatively weak-field sites. Hence, the Cr^{3+} exhibits only one excited state 4T_2 , which is inactivated by radiative transitions and non-radiative transitions from the thermal quench. Based on the obtained results, the maximum relative temperature sensitivity coefficients are $0.76\%~{\rm K}^{-1}$ at 498 K for the 717 nm emission and $0.47\%~{\rm K}^{-1}$ at 351 K for the 1 μm emission. This provides the possibility of developing a dual mode temperature sensor with high precision only using a single material.

Received 1st October 2017 Accepted 23rd October 2017

DOI: 10.1039/c7ra10864h

rsc.li/rsc-advances

Introduction

In recent years, optical temperature sensors have been widely applied in electrical power, chemical, metallurgical and other fields due to their advantages in anti-electromagnetic interference and high sensitivity. ¹⁻³ In order to further improve the accuracy and extend the operating temperature regions of optical temperature sensors, researchers have attempted to utilize multi-active-center doped material systems or new host materials for doping active-center ions. ⁴⁻⁸ These attempts involve a variety of temperature sensing mechanisms, providing ample valuable inspiration for the design of new types of temperature sensors. Among the various types of optical temperature sensors, luminescence-lifetime-based sensors make up a large proportion due to their intrinsic immunity to

the influence of external conditions such as those of the excitation beams and optical fiber transmission efficiencies. Trivalent chromium (Cr³⁺) ions, with the [Ar]3d³ electron configuration, have been widely applied as temperature sensing probes due to their diversity in temperature-dependent lifetimes, which vary with the different host materials used.9-11 Three equivalent d-electrons in the free Cr3+ ion lead to the spectral terms ⁴F (ground state), ⁴P and ²G (excited states). In crystals or glasses, the electrostatic interactions between the delectrons and ligand atoms can modify the spectral terms and induce the splitting of the d-orbital, where ⁴F would split into the 4T_1 and 4T_2 states and 2G would split into the 2E , 2T_1 , 2T_2 and ²A₂ states. On the basis of crystal field theory, ^{12,13} the optical properties of Cr3+ ions can be manipulated by the coordination of the host lattice or matrix particularly the atoms in the first coordination sphere. This leads to adjustable lowest excited states for the Cr³⁺ ions in various crystal fields. According to the Tanabe-Sugano diagram, 2E acts as the lowest excited state of Cr³⁺ at a high crystal field strength and is related to a narrowband red emission (~700 nm) due to the parity and spin doubly forbidden ²E \rightarrow ⁴A₂ transition with a long photoluminescence (PL) lifetime. Furthermore, ⁴T₂ would act as the lowest energy state at a low crystal field strength and results in

[&]quot;State Key Laboratory of Silicon Materials, Department of Materials Science and Engineering, Zhejiang University, Hangzhou 310027, China. E-mail: qiaoxus@zju.edu.cn; changjian-wang@zju.edu.cn

^bUMR-CNRS 6512 "Verres & Ceramiques", Institut de Chimie de Rennes, Universite de Rennes 1, Campus de Beaulieu, 35042 Rennes Cedex, France

[†] Electronic supplementary information (ESI) available. See DOI: 10.1039/c7ra10864h

RSC Advances Paper

a broad-band near-infrared (NIR) emission (\sim 1 µm) due to the parity-forbidden but spin-allowed $^4T_2 \rightarrow ^4A_2$ transition with a relatively short PL lifetime. Therefore, Cr^{3+} could be a good candidate for dual mode temperature sensing by coordination into different phases with significantly different strength crystal fields in multi-phase materials, such as glass-ceramics. 5,14

Oxyfluoride glass-ceramics¹⁵⁻¹⁷ have been considered as ideal hosts for various luminescence-active ions due to their high thermal and mechanical stability originating from the oxide glass matrix as well as their excellent spectroscopic merits related to the homogenously precipitated fluoride nanocrystals. Using a convenient heat treatment strategy, the crystal size and crystallinity can be easily controlled. Along with the evolution of both the phase and microstructure, the coordination of Cr³⁺ ions in different sites can be executed. Using this manipulation, one can design the crystal field around the Cr³⁺ ions and then adjust the spectroscopic behavior of the resulting materials.¹⁸

In this paper, Cr^{3+} -doped oxyfluoride glass-ceramics with homogeneously distributed cubic $CaF_2: Cr^{3+}$ nanocrystals were prepared upon annealing $50SiO_2-20Al_2O_3-30CaF_2$ glass. Two significantly different Cr^{3+} sites in the glass-ceramics were identified via PL spectroscopy and assigned to the O- and F-coordinated sites with red and NIR emissions, respectively. It follows that the temperature dependent PL lifetimes of Cr^{3+} at the different sites are both suitable for temperature sensing and can be proposed as a dual mode temperature sensing method requiring only the Cr^{3+} -singly-doped glass-ceramics.

2. Experimental procedure

Oxyfluoride glass with the composition $50 \text{SiO}_2 - 20 \text{Al}_2 \text{O}_3 - 29.95 \text{CaF}_2 - 0.05 \text{CrF}_3$ (in mol%, named as G) was prepared using a melt-quenching method. The appropriate batch of high purity (3 N) raw materials (silica, alumina, calcium fluoride and chromium fluoride) was placed in a covered corundum crucible and melted at 1500 °C for 45 min in air. Plain glasses were obtained by quenching the melt between two brass plates. Then, the subsequent crystallization temperatures (580 °C, 600 °C, 620 °C and 640 °C) were selected between the glass transition temperature (T_g) and the first crystallization temperature (T_{x1}) (Fig. S1†). The glass-ceramics GC580, GC600, GC620 and GC640, named after their annealing temperature, were obtained by annealing the glass at the abovementioned temperatures for 2 h in the air.

Differential thermal analysis (DTA) measurements were carried out on a CDR-1 differential thermal analyzer with a fixed specimen weight of 60 mg. X-ray diffraction (XRD) measurements were performed on a DIMAX-RA X-ray diffractometer (Rigaku Corporation, Tokyo, Japan) using Cu-K $_{\alpha}$ radiation at a scan rate of 2° min $^{-1}$. Transmission electron microscopy (TEM) and high resolution transmission electron microscopy (HRTEM) measurements were conducted to check the fine crystal structure using a CM200 (Philips, Eindhoven, the Netherlands) microscope. Photoluminescence (PL) spectra, including the excitation spectra, emission spectra and temperature dependent luminescence decay curves, were collected

using a FLSP920 spectrometer (Edinburgh Instrument Ltd., Livingston, UK) equipped with a TAP-02 temperature controller.

Results and discussion

3.1 Phase and microstructure

The glass-ceramics have a typical two-phase structure, where the cubic CaF2 lattice grew up to the nanoscale in the glass matrix and Cr3+ enlarged the lattice as an interstitial dopant. As shown in the XRD patterns (Fig. 1(a)), the as-quenched glass (sample G) exhibits a typical amorphous feature without any sharp diffraction peaks. In contrast, the glass-ceramics show sharp XRD peaks and the diffraction intensity became stronger upon increasing the annealing temperature, indicating the precipitation of FCC (face centered cubic) structured CaF₂ (JCPDS # 35-0816). Calculated using the Scherrer equation, the average crystal size could be estimated to be about 10, 13, 15 and 20 nm for GC580, GC600, GC620 and GC640, respectively. Moreover, the higher annealing temperatures also led to a higher crystallinity of CaF2 in the glass-ceramics. Furthermore, the diffraction peaks of the FCC CaF2 crystals in the investigated glass-ceramics shifted to lower diffraction angles (2θ) as compared to those of the standard JCPDS card (# 35-0816). For GC620, the calculated lattice parameter of the precipitated nanocrystals was 5.490 Å, which was higher than the standard value (5.463 Å). This was clear evidence of crystal lattice expansion, indicating the enrichment of Cr³⁺ ions into the CaF₂ lattice. It was unlikely that the Cr³⁺ (0.62 Å) would substitute Ca^{2+} (1.2 Å) due to the related lattice shrinkage effect. From the data obtained for the Ca^{2+} radius (1.2 Å in octahedral




Fig. 1 X-ray diffraction patterns (a) and transmittance spectra (b) of the ${\rm Cr}^{3+}$ -doped glass and glass ceramics fabricated using different annealing procedures. The TEM (c) and HRTEM (d) images of the ${\rm Cr}^{3+}$ -doped glass-ceramics obtained after annealing at 600 °C for 2 h (GC600).

Paper

coordination) and F radius (1.23 Å in tetrahedral coordination), the largest radii of the ions occupying the tetrahedral and octahedral interstices in cubic CaF2 were calculated to be 0.27 Å and 0.50 Å, respectively. Hence, Cr3+ ions exhibit a higher probability to occupy the octahedral interstice and enlarge the octahedron. In addition, the glass and the glass-ceramics obtained upon annealing at temperatures lower than 600 °C (GC580 and GC600) maintain high transparency in the visiblelight spectral region (Fig. 1(b)). However, in annealing at temperatures higher than 620 °C (GC620 and GC640), the glassceramics apparently lose their transparency. This was due to the large crystal size and crystallinity of the precipitated CaF2 in GC620 and GC640 (Table 1). In the transmittance spectra, two visible absorption bands were assigned to the ${}^4A_2 \rightarrow {}^4T_1$ (centered at 440 nm) and ${}^{4}A_{2} \rightarrow {}^{4}T_{2}$ (centered at 640 nm) energy level transitions of the Cr³⁺ ions Fig. 1(b).

The transmission electron microscopy (TEM, Fig. 1(c)) and high-resolution TEM (HRTEM, Fig. 1(d)) images display the precipitated CaF2 nanocrystals in GC600 with crystal sizes of \sim 10-15 nm, which are dispersed homogeneously in the glass host. This is consistent with the crystal size calculated from the XRD patterns using the Scherrer equation. The CaF₂ nanocrystals in the HRTEM image exhibited a well-defined lattice structure, and the interplanar spacing was calculated to be 0.3215 nm using a fast Fourier transform (FFT) algorithm. The interplanar spacing corresponds to the (111) plane of cubic CaF₂ (0.3155 nm, JCPDS # 35-0816). Similar to the XRD results, the calculated interplanar spacing (d = 0.3215 nm in Fig. 1(d)) was larger than the standard value. This indicates that a number of Cr3+ ions have entered the precipitated CaF2 crystalline phase, occupied the octahedral interstice, and enlarged the interplanar spacing.

3.2 Photoluminescence (PL)

The PL emission spectra (Fig. 2(a) and (c)) of the glass and glass-ceramics show different broad emission bands centered at 717 nm and 1 μ m when excited at 296 nm and 464 nm, respectively. Here, the sharp zero-phonon lines (R-lines at ~700 nm), observed due to the $^2E \rightarrow ^4A_2$ transition, could not be found in the spectra (Fig. 2(a)), which could be because the glass matrix inhomogenously broadened the zero-phonon lines. ¹⁹ Thus, the emission may be assigned to 2E , $^2T_1 \rightarrow ^4A_2$, while the 1 μ m emission may be attributed to $^4T_2 \rightarrow ^4A_2$. It was believed that these two clearly distinguishable emissions were related to the different Cr^{3+} sites coordinated with O^{2-} (717 nm) and F^{-} (1 μ m) in the glass and glass-ceramics, respectively. ²⁰ This will be further discussed in Section 3.3. By monitoring the emission at 717 nm, three broad excitation bands were recorded centered at

 ${\bf Table~1}~{\bf The~crystal~size}$ and crystallinity of the ${\bf Cr^{3+}}$ ion doped glass-ceramics

	GC580	GC600	GC620	GC640
Crystal size (nm)	10.4 ± 1.1		15.5 ± 1.1	20.5 ± 1.3
Crystallinity (%)	17.0 ± 0.5		31.6 ± 0.5	35.6 ± 0.6




Fig. 2 The PL emission and excitation spectra (a, c) as well as the PL decay curves (b, d) of the Cr^{3+} -doped glass-ceramics fabricated using the different annealing procedures: (a and b) by exciting at 296 nm and monitoring at 717 nm; (c and d) by exciting at 464 nm and monitoring at 1 μ m.

296 nm, 419 nm and 586 nm, corresponding to charge transfer band, Cr^{3+} : ${}^4\mathrm{A}_2 \to {}^4\mathrm{T}_1$ transition and Cr^{3+} : ${}^4\mathrm{A}_2 \to {}^4\mathrm{T}_2$ transition, respectively. By monitoring at 1 μ m, the three excitation bands corresponding to charge transfer band, Cr^{3+} : ${}^4\mathrm{A}_2 \to {}^4\mathrm{T}_1$ transition and Cr^{3+} : ${}^4\mathrm{A}_2 \to {}^4\mathrm{T}_2$ transition still exist. However, all three bands were red-shifted to longer wavelengths and located at 306 nm, 438 nm and 617 nm. As the annealing temperature was increased, the 717 nm emission was improved very limitedly; however, the 1 μ m emission intensity showed a significant enhancement. This could be due to the enhancement of the O^{2-} or F^- coordination of Cr^{3+} during the growth of the new phase (CaF_2 nanocrystals).

The PL decay curves were recorded by monitoring the emission at 717 nm or 1 μ m, as shown in Fig. 2(b) and (d). The PL decay curves were best fitted to double-exponential functions, which could be described by the following equation:

$$I(t) = A_1 \exp\left(-\frac{t}{\tau_1}\right) + A_2 \exp\left(-\frac{t}{\tau_2}\right),\tag{1}$$

where τ_1 and τ_2 are the long- and short-decay components respectively, and parameters A_1 and A_2 are fitting constants. According to eqn (1), the average lifetime $\langle \tau \rangle$ is given by:

$$\langle \tau \rangle = \frac{A_1 \tau_1^2 + A_2 \tau_2^2}{A_1 \tau_1 + A_2 \tau_2}.$$
 (2)

According to eqn (2), the average lifetimes of the 717 nm and 1 μ m luminescence were evaluated to be stable at about 1.6–1.7 ms and 22–23 μ s, respectively. The average lifetime of 717 nm was much longer than that of 1 μ m, which was consistent with assigning the 717 nm emission to the 2 E, 4 T₂

RSC Advances Paper

→ ⁴A₂ transition (partiy- and spin-forbidden for ²E) and assigning the 1 μm emission to the ${}^4T_2 \rightarrow {}^4A_2$ transition (parity-forbidden but spin-allowed).

3.3 O²⁻- or F⁻ coordination

Fluorosilicate glass probably constitutes both silicate and fluoride glassy matrices.21 Hence, the glass and glass-ceramics could provide F- and O-coordinated sites for Cr3+. On one hand, the silicate matrix is a random network of [SiO₄] tetrahedra, to which modifiers such as CaO were added to break up the networks and stabilizers such as Al₂O₃ were added to prevent crystallization. 19 Breakage of the Si-O covalent bonds by the modifiers produce approximately octahedral arrangements of O²⁻. The Cr³⁺ ions prefer to occupy these octahedral sites rather than the tetrahedral sites. On the other hand, the fluoride matrix formed by the [AlF₆] octahedral and polyhedral [CaF₈] also exist in the fluorosilicate glass host, where the Cr3+ ions can easily substitute Al³⁺ to occupy the octahedral sites. Alkaline earth fluorides such as CaF2 act as modifiers in the fluoride matrix and are easily crystallized from the matrix. According to the phase and microstructural analysis (Fig. 1), the Cr³⁺ ions also enter the precipitated CaF2 crystalline phase of the glass ceramics, occupying the octahedral interstice and enlarging the interplanar spacing. As a result, the Cr3+ ions were octahedrally coordinated with O2- and F-, and displayed two different luminescence behaviors. Upon increasing the annealing temperature, the crystallinity of the precipitated CaF₂ gradually increases, so that more Cr3+ ions are surrounded by the CaF2 lattice and subsequently, the 1 µm emission was enhanced (Fig. 2(c)). The F/O ratio of the residual glassy phase was reduced to a lower level due to the crystallization of CaF2 and thus, the O²⁻ coordination environment was significantly enhanced. However, such an O2- coordination enhancement was too small to significantly influence the PL intensity (Fig. 2(a)).

The energy level structure of Cr³⁺ is highly dependent on the crystal field strength and determines the different PL behaviour of the O-coordinated and F-coordinated Cr3+ ions. The energy level structures of transition metal ions are usually determined by the relative strengths of the octahedral crystal ligand field splitting parameter, D_q , and the Racah parameters, B and C. Solutions to the multi-electron crystal-field Hamiltonian are represented on Tanabe-Sugano diagrams, 22,23 in which the normalized multiplet energies, $E(\Gamma)/B$, are plotted as a function of D_0/B , for a constant value of C/B, where Γ denotes the irreducible representation of the electronic state. In inorganic glass or crystals, the Cr³⁺ions prefer to occupy the sites exhibiting a nearly perfect octahedral symmetry because of the strong ligand field stabilization energy of Cr3+ in a six-fold coordination geometry.24 As illustrated in the Tanabe-Sugano diagram (Fig. 3(a)), in an octahedral crystal field the ⁴F of Cr³⁺ will split into ⁴A₂, ⁴T₂ and ⁴T₁, while ²G would split into ²E, ²T₁, ²T₂ and ²A₁. The ⁴A₂ state has the lowest energy and serves as the ground state. The energy difference between ²E and ²T₁ or ²T₂ and ⁴A₂ was almost constant or varies slightly in all the fields; however, the energy difference between 4T2 and 4A2 varies significantly




Fig. 3 Tanabe-Sugano diagram of Cr³⁺ ions in the octahedral crystal field (a); energy levels of the Cr^{3+} ions coordinated with F^- (b) in a low crystal field strength and with O^{2-} in an intermediate crystal field strength (c).

upon changing the crystal field. The studies of both Tanabe^{25,26} and Casalboni²⁷ clearly show the relationship between the energy of the different excited states of Cr^{3+} ions and D_a/B . In weak crystal-field sites, where $D_a/B < 2.3$, the lowest excited state was an orbital triplet ⁴T₂, from which broadband PL is observed due to the enhancement of the phonon assisted ${}^4T_2 \rightarrow {}^4A_2$ transitions. For strong crystal fields $(D_0/B > 2.3)$, the lowest excited state was changed to ²E and the spectrum consists of narrow zero-phonon lines (R lines) with vibrationally induced sidebands due to the ${}^{4}T_{2} \rightarrow {}^{4}A_{2}$ transitions. For intermediate crystal fields $(D_0/B \approx 2.3)$, mixing between 4T_2 and 2E occurs and the observed photoluminescence spectrum, even at low temperature, is a superposition of the broad ${}^4\Gamma_2 \rightarrow {}^4A_2$ band on the ${}^{2}E \rightarrow {}^{4}A_{2}$ R line and its phonon sideband.

The strength D_q of the octahedral crystal field and the Racah parameter B can be determined from the peak energies of the ${}^{4}A_{2} \rightarrow {}^{4}T_{2}$ and the ${}^{4}A_{2} \rightarrow {}^{4}T_{1}$ transitions. ²⁸ In octahedral symmetry, the energy difference between the 4A2 and 4T2 states is equal to $10D_q$, which is measured from the peak energy (ν_1) of the ${}^{4}A_{2} \rightarrow {}^{4}T_{2}$ absorption band:

$$D_{\mathbf{q}} = \frac{v_1}{10}.\tag{3}$$

The value of B is determined from the energy value (ν_1) of ${}^4\text{A}_2 \rightarrow {}^4\text{T}_2$ and the energy value (ν_2) of ${}^4\text{A}_2 \rightarrow {}^4\text{T}_1$, is given by

$$B = \frac{(2v_1 - v_2)(v_2 - v_1)}{3(9v_1 - 5v_2)}. (4)$$

According to the absorption spectra (Fig. 1(b)), the glass and the glass-ceramics have almost the same average values for ν_1 and ν_2 , and thus have the same values of $D_q = 1571.3 \text{ cm}^{-1}$, B =734.1 cm⁻¹ and $D_0/B = 2.14$.

As a matter of fact, the PL spectra (Fig. 2) revealed two types of Cr³⁺ sites: the O²⁻ octahedrally coordinated sites (centered at 717 nm) and the F⁻ octahedrally coordinated sites (centered at 1 μm) in the glass and glass-ceramics. Herein, in order to evaluate the crystal field strengths of the [CrO₆] and [CrF₆] octahedra, the PL excitation peak wavelengths were used to deduce the values of ν_1 and ν_2 ; then, the D_q/B values were evaluated as 2.5 and 2.3

Paper

for [CrO₆] and [CrF₆], respectively. Thus, the energy level diagrams of the F⁻ octahedrally coordinated (Fig. 3(b)) and O²⁻ octahedrally coordinated (Fig. 3(c)) sites were elicited from the Tanabe-Sugano diagram (Fig. 3(a)). O2- coordination has an intermediate crystal field with first excited states of ²E and ²T₁, while F⁻ coordination has a weak crystal field with a lower first excited state, ⁴T₂. This was consistent with the increasing trends of D_0/B correlated with the anion packing densities along the

following sequence: fluoride \rightarrow silicate \rightarrow borate. Silicate glasses provide relatively strong-field sites, while fluoride and fluorozirconate glasses provide weak-field sites only and the luminescence observed is only a broad ${}^{4}T_{2} \rightarrow {}^{4}A_{2}$ band with a large Stokes red-shift. 19,20,28 Accordingly, when compared with O-coordinated Cr³⁺ (717 nm), the PL emission of F-coordinated Cr³⁺ ions show a red-shift to 1 µm and shorter PL lifetimes. Such a situation was also clearly observed with the excitation bands. When monitored at 1 µm, the three broad excitation bands show red-shifts to longer wavelengths when compared with those monitored at 717 nm. In addition, the charge transfer band monitored by the 1 um emission was much weaker than those monitored by the 717 nm emission. This can be deduced from the larger electron density related to O²⁻ compared to F⁻.

3.4 Temperature sensing performance

To explore the possible applications of dual-model temperaturedependent decay lifetimes in optic temperature sensors, the PL decay curves for the Cr3+-doped GC640 sample from room temperature to about 300 °C (Fig. 4(a) and (b)) were recorded by monitoring at 717 nm and 1 µm. The evaluated lifetimes for both Cr³⁺ sites appear to decrease with temperature (Fig. 4(c) and (d)). Such temperature dependent relationships are mainly due to the thermally activated repopulation between the ²E and ${}^{4}\text{T}_{2}$ states. The ${}^{2}\text{E} \rightarrow {}^{4}\text{A}_{2}$ transition is doubly forbidden by parity




Fig. 4 The 296 nm excited 717 nm luminescence decay curves (a) and the 464 nm excited 1 µm luminescence decay curves (b) obtained for GC640 at different temperature. The fitted relationships of the luminescence lifetimes of Cr3+ and temperature (c and d), where the insets show the sensitivity at the investigated temperature ranges




Fig. 5 Simplified energy level diagrams of Cr³⁺ at the different sites in the investigated glass-ceramics: (a) O-coordinated sites and (b) Fcoordinated sites

and spin, which has a longer decay time than the ${}^{4}T_{2} \rightarrow {}^{4}A_{2}$ transition (spin-allowed).

For O-coordinated sites, the ²E, ²T₁, ⁴T₂ and ⁴A₂ energy states were proposed as interrelated, as Fig. 5(a) illustrates, in a configuration coordinate model, where ²E serves as the lowest excited state and easily intersects with the upper state, ${}^{4}T_{2}$, by the assistance of only a few phonons. Upon increasing the temperature, more electrons repopulate from ²E to ⁴T₂, resulting in short PL decay lifetimes.9 Theoretically, the total number of excited ions can be expressed as: $n = n_E + n_T$, where n_E and n_T represent the number of ions at ²E and ⁴T₂,respectively. The particles at the two levels follow the Boltzmann distribution: $\frac{n_{\rm E}}{n_{\rm T}} = C \; \exp(-\Delta E/k_{\rm B}T)$, where *C* is the degeneration ratio of $^2{\rm E}$ to ${}^4\Gamma_2$, with a value of 3. The decay rate of the total excited state ions is represented by the following expression: $rac{dn}{dt}=-rac{1}{ au}n=-rac{1}{ au_E}n_E-rac{1}{ au_T}n_T.$ Therefore, by solving the equation: $-\frac{1}{\tau}n = -\frac{1}{\tau_{\rm E}}n_{\rm E} - \frac{1}{\tau_{\rm T}}n_{\rm T}$, the lifetime was obtained as:

$$\tau = \tau_{\rm E} \frac{1 + 3 \exp(-\Delta E/k_{\rm B}T)}{\tau_{\rm E} + 3 \exp(-\Delta E/k_{\rm B}T)}.$$
 (5)

The sensitivity could be calculated using the following equation:

$$S = \left| \frac{1}{\tau} \frac{d\tau}{dT} \right| = 3 \exp(-\Delta E/k_{\rm B}T) \frac{\Delta E}{k_{\rm B}T^2} \times \left(\frac{1}{1+3 \exp(-\Delta E/k_{\rm B}T)} - \frac{\tau_{\rm E}}{\tau_{\rm T} + \tau_{\rm E} \exp(-\Delta E/k_{\rm B}T)} \right). \tag{6}$$

Thereby, the PL lifetime data of 717 nm from 298.35 K to 573.25 K were well fitted as the solid line using the least-square method, as shown in Fig. 4(c). The correlation coefficient (R^2) reached 0.99. The parameters $\tau_{\rm E}$, $\tau_{\rm T}$ and ΔE were determined to be 1.835 ms, 0.008 ms and 2044.5 cm⁻¹, respectively. In addition, the sensitivity curve reaches a maximum of 0.76% K⁻¹ at 498 K, as shown in the inset of the Fig. 4(c).

For the F-coordinated sites, the ²E, ²T₁, ⁴T₂ and ⁴A₂ energy states were proposed as interrelated using a configuration **RSC Advances**

Table 2 The optical thermometry performance of some Cr³⁺ ion-doped materials

Materials	$\Delta E \left(\mathrm{cm}^{-1} \right)$	$T_{\max}\left(\mathbf{K}\right)$	S_{\max} (% K^{-1})	Ref.
$Y_3Al_5O_{12}:Cr^{3+}$	_	_	0.50	31
$LiAl_5O_8: Cr^{3+}$	_	447	0.83	32
Ruby $(Al_2O_3: Cr^{3+})$	1637	390	0.48	33
$LiSrAlF_6: Cr^{3+}$	4557	333	1.80	34
$Ga_2O_3: Cr^{3+}$ (in glass-ceramics)	1215	386	0.59	5
O-coordinated Cr ³⁺ (in glass-ceramics)	2044	498	0.76	This work
F-coordinated Cr ³⁺ (in glass-ceramics)	898	351	0.47	This work

coordinate model as illustrated in Fig. 5(a), where ⁴T₂ serves as the lowest excited state. The large Stokes shift and weak crystal field at the F-coordinated sites enhance the decay rate of (W_{NR}) from the 4T2 excited state to the 4A2 ground state. It thus becomes a predominant factor to significantly reduce the 1 µm PL lifetime as shown in Fig. 4(b). Theoretically, the Mott-Seitz model was used to describe this mechanism quantitatively.29 The total transition probabilities of the ⁴T₂ state are comprised transition of radiative $(W_{\rm R})$ and non-radiative $(W_{\rm NR})$ probabilities:

$$\frac{1}{\tau(T)} = \frac{1}{\tau_{\rm R}} + \frac{1}{\tau_{\rm NR}},\tag{7}$$

where τ_R is the radiative lifetime and τ_{NR} is the non-radiative lifetime. As illustrated in Fig. 5(b), an electron in the ⁴T₂ state would cross the barrier ΔE to the ground state by absorbing a certain amount of phonons.³⁰ We assumed that τ_R was independent of temperature, while τ_{NR} is dependent of temperature; the relationship between τ_{NR} and temperature can be expressed using the Arrhenius equation:

$$\frac{1}{\tau_{\rm NR}} = \frac{1}{\tau_{\rm NR}(0)} \exp(-\Delta E/k_{\rm B}T),\tag{8}$$

where $\tau_{NR(0)}$ is the non-radiative decay time at 0 K, ΔE is the energy barrier mentioned above and $k_{\rm B}$ is the Boltzmann constant. Accordingly, when the temperature increases, the non-radiative decay will become stronger. Through the deformation of the formulae (7) and (8), the total (experimentally measured) lifetime can be written as:

$$\tau(T) = \frac{\tau_{\rm R}}{1 + \frac{\tau_{\rm R}}{\tau_{\rm NR(0)}} \exp(-\Delta E/k_{\rm B}T)},\tag{9}$$

Then, the sensitivity was calculated using the following equation:

$$S = \left| \frac{1}{\tau} \frac{\mathrm{d}\tau}{\mathrm{d}T} \right| = \frac{\tau_{\mathrm{R}}}{\tau_{\mathrm{R}} + \tau_{\mathrm{NR}(0)} \exp(\Delta E / k_{\mathrm{B}} T)} \frac{\Delta E}{k_{\mathrm{B}} T^{2}}.$$
 (10)

We used this equation to fit the lifetime data of the 1 μ m emission observed for the GC640 sample. The solid line shown in Fig. 4(d) was the least-squares curve fitting to the lifetime data from 298.25 K to 498.15 K. Impressively, the correlation coefficient (R^2) reached as high as 0.999. This not only expounded the temperature-dependence of the lifetime in the

experimental temperature range but also guaranteed the effectiveness of the temperature sensing. Through the fitting, the corresponding parameters τ_R , τ_{NR} and ΔE were determined to be 32.814 μ s, 0.997 μ s and 898.3 cm⁻¹, respectively. In addition, the sensitivity curve reaches a maximum of 0.47% K⁻¹ at 351 K as shown in the inset of the Fig. 4(c).

Based on the abovementioned temperature sensing parameters, comparable performances could be expected for optical thermometries upon introducing the Cr3+-doped fluorosilicate glass-ceramic materials. As a comparison, the temperature sensing parameters of some typical materials reported in the literature are listed in Table 2. The O-coordinated Cr³⁺ in the glass-ceramics exhibit maximum sensitivity ($S_{\text{max}} = 0.76\% \text{ K}^{-1}$), which was slightly lower than that observed for LiAl₅O₈: Cr³⁺, but still better than those reported for Y₃Al₅O₁₂: Cr³⁺, Al₂O₃-: Cr3+ (ruby) and Ga2O3: Cr3+ in glass-ceramics and with a higher work temperature ($T_{\text{max}} = 498 \text{ K}$). The F-coordinated Cr3+ in the glass-ceramics showed the maximum sensitivity $(S_{\text{max}} = 0.47\% \text{ K}^{-1})$ at $T_{\text{max}} = 351 \text{ K}$, which was similar to that observed in Al₂O₃: Cr³⁺ (ruby), so it could also be a good candidate material for optical thermometry. When compared with crystalline and ceramic materials, the glass-ceramics have the further advantages of good designability, easy molding, cost-efficient and so on. Therefore, these types of Cr3+-doped glass-ceramics are very promising candidates for developing a type of dual mode optical thermometry.

Conclusion

In fluorosilicate glass-ceramics comprising homogenous cubic CaF₂ nanocrystals, Cr³⁺ions occupied two different types of sites: one was the O-coordinated octahedral sites in the residual glass phase and the other was the F-coordinated octahedral sites were distributed not only in the residual glass phase but also in the nanocrystalline CaF2 phase. A certain number of Cr³⁺ions entered the precipitated CaF₂ nanocrystals, occupying the octahedral interstice and induced an expansion of the fluorite cube lattices. The 717 nm emission was derived from the O-coordinated octahedral sites, while the 1 µm super-broad emission was assigned to the F-coordinated octahedral sites. Upon annealing, the crystal size and crystallinity of the CaF₂ nanocrystals could be enlarged, thus the F-coordinated octahedral Cr³⁺ sites were enhanced and the PL at 1 μm became stronger.

Paper RSC Advances

The O-coordinated sites were relatively strong crystal field sites, so the 717 nm emission originates from the radiative transitions of the two thermally coupled ²E and ⁴T₂ energy levels of Cr³⁺. In contrast, the F-coordinated sites were relatively weakfield sites, thus ⁴T₂ alternatively served as the lowest excited state and a low vibrational level of ⁴T₂ was easily tunneled to a high vibrational level of the ground state as a result of a thermal quench in non-radiative transition. Accordingly, the temperature dependent PL lifetimes could be theoretically described by eqn (5) and (9). By mean square fitting methods, the maximum relative temperature sensitivity coefficients were $0.76\%~\mathrm{K^{-1}}$ at 498 K for the 717 nm PL lifetime and $0.47\%~\mathrm{K^{-1}}$ at 573 K for the 1 µm PL lifetime. These results are comparable with some other typical optical temperature sensing materials, providing evidence of the potential to apply glass-ceramics in highly sensitive, dual mode, self-calibrated PL-lifetime-based temperature sensing.

Conflicts of interest

There are no conflicts to declare.

Acknowledgements

This work was supported by the National Natural Science Foundation of China (No. 51672243), the Program for International S&T Cooperation Projects of China (No. 2014DFB50100), Zhejiang Provincial Natural Science Foundation of China (No. LY16E020003) and the Fundamental Research Funds for the Central Universities (No. 2016QNA4005; No. 2016FZA4007). The authors are very grateful to the support of their research team and for involving one of the authors (Shuo Cui) in the sample preparation and spectral measurements. Associate Prof. Xvsheng Qiao gave a detailed and patient guidance to this work.

References

- 1 X. Wang, Q. Liu, Y. Bu, C. S. Liu, T. Liu and X. Yan, *RSC Adv.*, 2015, **105**, 86219–86236.
- 2 X. D. Wang, O. S. Wolfbeis and R. J. Meier, *Chem. Soc. Rev.*, 2013, 42, 7834–7869.
- 3 A. H. Khalid and K. Kontis, Sensors, 2008, 8, 5673-5744.
- 4 M. D. Chambers and D. R. Clarke, *Annu. Rev. Mater. Res.*, 2009, **39**, 325–359.
- 5 D. Chen, Z. Wan and Y. Zhou, Opt. Lett., 2015, 40, 3607–3610.
- 6 A. K. Singh, P. Shahi, S. B. Rai and B. Ullrich, RSC Adv., 2015, 21, 16067–16073.
- 7 H. Lu, H. Hao, G. Shi, Y. Gao, R. Wang, Y. Song, Y. Wang and X. Zhang, *RSC Adv.*, 2016, **60**, 55307–55311.
- 8 S. Liu, S. Liu, M. Zhou, X. Ye, D. Hou and W. You, *RSC Adv.*, 2017, **59**, 36935–36948.

- 9 Z. Zhang, K. T. V. Grattan and A. W. Palmer, *Phys. Rev. B*, 1993, 48, 7772–7778.
- 10 Y. L. Hu, Z. Y. Zhang, K. T. V. Grattan, A. W. Palmer and B. T. Meggitt, Sens. Actuators, A, 1997, 63, 85–90.
- 11 Y. R. Shen and K. L. Bray, *Phys. Rev. B*, 1997, **56**, 10882–10891.
- 12 H.-H. Schmidtke and J. Degen, in *Stereochemistry and Bonding*, Springer, 1989, pp. 99–124.
- 13 A. Luci, T. Castrignano, U. Grassano, M. Casalboni and A. Kaminskii, *Phys. Rev. B*, 1995, 51, 1490.
- 14 D. Chen, Z. Wan, Y. Zhou, X. Zhou, Y. Yu, J. Zhong, M. Ding and Z. Ji, *ACS Appl. Mater. Interfaces*, 2015, 7, 19484–19493.
- 15 M. J. Dejneka, J. Non-Cryst. Solids, 1998, 239, 149-155.
- 16 Y. Wang and J. Ohwaki, Appl. Phys. Lett., 1993, 63, 3268-3270
- 17 C. Liu and J. Heo, J. Am. Ceram. Soc., 2012, 95, 2100-2102.
- 18 P. I. Macfarlane, K. Holliday, J. Nicholls and B. Henderson, *J. Phys.: Condens. Matter*, 1995, 7, 9643.
- 19 B. Henderson, M. Yamaga, Y. Gao and K. O'Donnell, *Phys. Rev. B*, 1992, 46, 652.
- 20 F. Rasheed, K. O'Donnell, B. Henderson and D. Hollis, *J. Phys.: Condens. Matter*, 1991, 3, 3825.
- 21 J. Zhao, R. Ma, X. Chen, B. Kang, X. Qiao, J. Du, X. Fan, U. Ross, C. Roiland and A. Lotnyk, *J. Phys. Chem. C*, 2016, 120, 17726–17732.
- 22 S. Sugano, Multiplets of transition-metal ions in crystals, Elsevier, 2012.
- 23 B. Henderson and G. F. Imbusch, *Optical spectroscopy of inorganic solids*, Oxford University Press, 2006.
- 24 J. Fernández, M. Illarramendi, R. Balda, M. Arriandiaga, J. Lucas and J. Adam, J. Non-Cryst. Solids, 1991, 131, 1230– 1234.
- 25 Y. Tanabe and S. Sugano, J. Phys. Soc. Jpn., 1954, 9, 753-766.
- 26 Y. Tanabe and S. Sugano, J. Phys. Soc. Jpn., 1954, 9, 766-779.
- 27 M. Casalboni, V. Ciafardone, G. Giuli, B. Izzi, E. Paris and P. Prosposito, *J. Phys.: Condens. Matter*, 1996, **8**, 9059.
- 28 F. Rasheed, K. O'Donnell, B. Henderson and D. Hallis, J. Phys.: Condens. Matter, 1991, 3, 1915.
- 29 L. Bøtter-Jensen, S. W. McKeever and A. G. Wintle, *Optically stimulated luminescence dosimetry*, Elsevier, 2003.
- 30 M. Ren, C. D. Brites, S.-S. Bao, R. A. Ferreira, L.-M. Zheng and L. D. Carlos, *J. Mater. Chem. C*, 2015, **3**, 8480–8484.
- 31 H. Aizawa, T. Katsumata, Y. Kiyokawa, T. Nishikawa, T. Sasagawa, S. Komuro, T. Morikawa, H. Ishizawa and E. Toba, *Measurement*, 2006, **39**, 147–152.
- 32 X. Li, G. Jiang, S. Zhou, X. Wei, Y. Chen, C. K. Duan and M. Yin, *Sens. Actuators, B*, 2014, **202**, 1065–1069.
- 33 H. Seat and J. Sharp, *IEEE Trans. Instrum. Meas.*, 2004, 53, 140–154.
- 34 Z. Zhang, K. Grattan and A. Palmer, *Optical Fiber Sensors Conference*, IEEE Xplore, 1992, pp. 93–96.