Chemical Science

EDGE ARTICLE

Cite this: Chem. Sci., 2018, 9, 5452

Received 19th April 2018 Accepted 30th May 2018 DOI: 10.1039/c8sc01778f

rsc.li/chemical-science

Introduction

Nanostructured layered tungsten diselenide $(WSe₂)$ materials, a class of newly emerging two dimensional (2D) transitionmetal dichalcogenide (TMD) nanomaterials, have attracted extensive interest in the development of sensors, $¹$ tunneling</sup> devices, $2,3$ transistors, $4,5$ optoelectronics,⁶ hydrogen evolution⁷⁻¹⁰ and flexible electronics^{11,12} due to their unique thermal, gassensitive, electrical, mechanical, photoelectrical and optical properties.¹³ WSe₂ materials are also promising candidates for

Dynamic tungsten diselenide nanomaterials: supramolecular assembly-induced structural transition over exfoliated two-dimensional nanosheets†

Adem Ali Muhabie[,](http://orcid.org/0000-0002-7195-208X)^b Ching-Hwa Ho, D^a Belete Tewabe Gebeyehu,^a Shan-You Huang,^a C[hih-](http://orcid.org/0000-0002-1605-6338)Wei Chiu,^b Juin-Yih Lai,^{ace} Duu-Jong Lee^{cde} and Chih-Chia Cheng^{D*a}

A simple and effective method for direct exfoliation of tungsten diselenide (WSe₂) into few-layered nanosheets has been successfully developed by employing a low molecular weight adeninefunctionalized supramolecular polymer (A-PPG). In this study, we discover A-PPG can self-assemble into a long-range, ordered lamellar microstructure on the surface of WSe₂ due to the efficient non-covalent interactions between A-PPG and WSe₂. Morphological and light scattering studies confirmed the dynamic self-assembly behavior of A-PPG has the capacity to efficiently manipulate the transition between contractile and extended lamellar microstructures on the surface of metallic 1T-phase and semiconducting 2H-phase WSe₂ nanosheets, respectively. The extent of WSe₂ exfoliation can be easily controlled by systematically adjusting the amount of A-PPG in the composites, to obtain nanocomposites with the desired functional characteristics. In addition, the resulting composites possess unique liquid–solid phase transition behavior and excellent thermoreversible properties, revealing the self-assembled lamellar structure of A-PPG functions as a critical factor to manipulate and tailor the physical properties of exfoliated WSe₂. This newly developed method of producing exfoliated WSe₂ provides a useful conceptual and potential framework for developing WSe₂-based multifunctional nanocomposites to extend their application in solution-processed semiconductor devices. **EDGE ARTICLE**
 (a) Check forundates

Consists, 2018, 9, 5422

Consists, 2018, 9, 5422

Consister and Consists and Consister and Consis

many optical and electrical applications due to their controllable band structure and intrinsic photoluminescence, features not found in graphene.¹⁴ The single layer of $WSe₂$ is composed of a 6.7 Å-thick slab of a Se-W-Se sandwich layer. Atomically-thin $WSe₂$ is unique as it is chemically homogeneous, but exhibits both a semiconducting 2H crystal structure and metallic 1T phase. The 2H phase, in which two layers per unit cell stack in hexagonal symmetry with a trigonal prismatic coordination, and the metastable 1T metallic phase, which possesses one-layer unit cell in tetragonal symmetry with octahedral coordination, are observed in 2D nanomaterials prepared by intercalationassisted-exfoliation.¹⁵ Recently, the exfoliation of $WSe₂$ nanosheets from pristine $WSe₂$ has attracted a great deal of attention, as understanding the adsorption properties of functional materials dispersed on the surface of $WSe₂$ is fundamental to enable rational control of surface functionalization, in order to generate high-efficiency optoelectronic devices for efficient hydrogen evolution, field-effect transistors and photodetectors/light emitting diodes.^{16,17} Hence, exfoliation techniques play a crucial role in the production of $WSe₂$ for a variety of applications.

^aGraduate Institute of Applied Science and Technology, National Taiwan University of Science and Technology, Taipei 10607, Taiwan. E-mail: cccheng@mail.ntust.edu.tw b Department of Materials Science and Engineering, National Taiwan University of Science and Technology, Taipei 10607, Taiwan

c Department of Chemical Engineering, National Taiwan University of Science and Technology, Taipei 10607, Taiwan

d Department of Chemical Engineering, National Taiwan University, Taipei 10617, Taiwan

e R&D Center for Membrane Technology, Chung Yuan Christian University, Chungli, Taoyuan 32043, Taiwan

[†] Electronic supplementary information (ESI) available: General methods, materials, and instrumental information are shown. See DOI: 10.1039/c8sc01778f

A number of synthetic methods have been developed to fabricate $WSe₂$ nanosheets, such as chemical vapor deposition, micromechanical cleavage, and chemical and sonicationassisted liquid phase exfoliation methods.² In principle, the chemical vapor deposition technique enables fabrication of macroscopic areas of TMD films, though generation of single continuous layers on the macroscopic scale remains challenging. The commonly used micromechanical method has low repeatability, precision and limited ability to control the thickness and sizes of the sheets during production of exfoliated WSe₂.¹⁸ Hence, many of the existing synthesis methods are not convenient; the scalability and practical applications of $WSe₂$ nanosheets are limited by their high cost, low yield, restacking and complex synthetic procedures. Design of an environmentally friendly, low-cost, efficient and simple fabrication technique remains a significant challenge, but would be enormously valuable for both research and commercial applications.¹⁹

Compared to the aforementioned methods, the sonicationassisted liquid phase exfoliation method is more promising,²⁰ as it can produce 2D nanosheets of high structural quality with stable, uniformly dispersed flakes.²¹⁻²³ However, the major limitation of liquid-phase exfoliation is that the $WSe₂$ nanosheets produced restack into a bulk structure via van der Waals interactions, which significantly limits extensive application of these nanomaterials.¹⁴ In order to resolve these problems and provide a realistic solution, it would be highly desirable to establish an efficient dispersal technique that effectively exfoliates $WSe₂$ into an organic solution in which restacking of dispersed $WSe₂$ is impeded, to enable the synthesis of highquality dispersed $WSe₂$ for a wide range of applications across many fields of engineering and science.^{15,16}

Non-covalently functionalized supramolecular polymers have been acquired from functional macromers, and exhibit tailorable physical properties and viscoelastic functionality due to the dynamic bonds between monomeric units.²⁴⁻²⁶ Recently, our research group discovered an ureido-cytosinefunctionalized supramolecular polymer, which we used to directly delaminate graphene from graphite into micrometersized few-layered sheets. Application of these supramolecular polymers for the production of 2D nanomaterials enabled wellcontrolled exfoliation, manipulation and successive dispersion of graphite to be easily achieved. The self-assembled lamellar microstructure of supramolecular polymers and electric conductivity of polymer-graphene composites have been characterized.²⁷ Subsequently, we developed a simple, efficient method for exfoliation of hexagonal boron nitride (h-BN) into few-layered nanosheets using adenine end-capped polypropylene glycol (A-PPG) as a dispersing and stabilizing agent, and confirmed A-PPG self-assembled into either lamellar or micelle structures on the surface of h-BN nanosheets via π – π stacking. Furthermore, A-PPG/h-BN composites exhibited welldefined phase transition behavior and excellent thermal stability over a wide temperature range due to the presence of the adenine moieties and their reversible hydrogen-bond interactions.²⁰ A-PPG is also a biocompatible stimuliresponsive polymer with potential for biomedical applications

Scheme 1 Chemical structures of the A-PPG macromer and schematic representation of the non-covalent liquid-phase exfoliation of WSe₂ nanosheets in the presence of A-PPG dispersant.

such as controlled drug delivery and bioimaging.²⁸ Based on our previous findings, the combination of A-PPG with $WSe₂$ represents a promising strategy for producing few-layer $WSe₂$ nanosheets at high efficiency via a simple process, with potential for various applications.

In the present study, we demonstrate A-PPG can be used successfully to assist high-efficiency liquid phase exfoliation of WSe₂ in tetrahydrofuran (THF) via ultrasonic treatment. Furthermore, morphological studies indicated formation of well-ordered lamellar nanostructures among the adsorbed A-PPG on the surface of $WSe₂$ strongly manipulates the selfassembly behavior and physical properties of exfoliated $WSe₂$ (Scheme 1). Moreover, adsorption of A-PPG on the surface of the 1T and 2H phases of $WSe₂$ led to a spontaneous structural transformation between extended and contracted lamellar microstructures, resulting in excellent microstructural stability and stable thermoreversible behavior in the bulk state. To date, there has been no reported example of the production of exfoliated $WSe₂$ nanosheets using a supramolecular polymer with the aim of efficiently manipulating contracted/expanded lamellar microstructures and achieving thermoreversible phase transition behavior on $WSe₂$ surfaces. Hence, employing the adenine-based supramolecular A-PPG for exfoliation of $WSe₂$ crystals provides a simple, efficient pathway towards the development of high-quality multifunctional exfoliated $WSe₂$ for a wide variety of semiconductor applications.

Results and discussion

A novel self-complementary adenine end-capped A-PPG was successfully prepared using a simple one-step synthesis method described in our previous work.²⁰ The synthesized A-PPG spontaneously assembled into a well-ordered lamellar nanostructure (with an interlamellar distance of 1.33 nm, determined by wide angle X-ray diffraction) due to supramolecular

polymerization of A-PPG via the doublet hydrogen bonding interactions between adenine moieties (Scheme 1).²⁰ Subsequently, the WSe_2 and A-PPG blend was sonicated in THF for 1 h at 25 °C. After ultrasonic treatment, exfoliated WSe₂ was scattered throughout the solvent, resulting in a dark brown dispersion (inset photograph i in Fig. 1a). The solution remained stable for over one month at room temperature with no obvious signs of precipitation, implying attachment of A-PPG to the $WSe₂$ sheets acts as a strong stabilizing agent against aggregation and re-stacking of single/few-layer $WSe₂$ nanosheets. In addition, unlike pure A-PPG solution, the 50/50 WSe₂/A-PPG composite solution demonstrated the Tyndall effect in THF (inset photograph ii in Fig. 1a); the path of the laser beam could be obviously seen within the solution due to scattering by the $WSe₂$ nanosheets – suggesting uniform dispersion of the exfoliated $WSe₂$ nanosheets – and exhibited red fluorescence due to the band transition after exfoliation.³⁰ Photoluminescence (PL) spectroscopy analyses of these composites in THF were employed using an excitation wavelength of 420 nm. The A and B excitonic absorption peaks shown in Fig. 1b are the result of optical transitions involving a spin–orbit split valence band and degenerate conduction band at the K point of the Brillouin zone.^{31,32} The two splitting absorption peaks, A $^{\prime}$ and B $^{\prime}$, in the WSe $_2$ /A-PPG composites are the result of the A and B peaks splitting due to inter- and intralayer effects induced by the noncovalent interaction between A-PPG and WSe₂. In addition, WSe₂/A-PPG composites exhibited an increase in the emission intensity of the excitonic absorption peak B and split exciton peaks (A $^{\prime}$ and B $^{\prime})$, indicating the flakes thinned to a few layers as the concentration of A-PPG increased. This result also implies that the increased loading of A-PPG favors the active phase formation of $WSe₂$. The $WSe₂$ band structure underwent an indirect-to-direct optical gap Openical Science

(Published on 4-PPG via distribution (Scheme), Published on 2018. Downloaded and 2018. Downloaded on 2018. Downloaded and 2018. Downloaded the stationary interaction (Scheme), reaching in a distribution (

Fig. 1 (a) UV-vis absorption spectrum for a THF dispersion of the 50/ 50 WSe₂/A-PPG composite (concentration, 0.5 mg mL $^{-1}$). The insets are photographs of (i) THF solutions of A-PPG (left) and WSe₂/A-PPG (right) and (ii) the same solutions illuminated from the right using a 650 nm laser beam. (b) PL and (c) Raman spectra of WSe₂ nanosheets with different contents of A-PPG. (d) Raman peak shift data extracted from peak frequency range (c).

transition when reduced in thickness to a few layers, which when exfoliated, yielded a 2D nanomaterial.^{33,34} Ultravioletvisible (UV-vis) spectra of the $50/50$ WSe₂/A-PPG composite (Fig. 1a) contained an absorption peak at 773 nm, a feature of the A exciton of WSe_2 (Fig. 1b) and attributed to the smallest direct excitonic transition in the $WSe₂$ layers, suggesting the potential of these layers for photothermal materials.³⁵ This observation also implies that the A-PPG macromer was stably adsorbed on the $WSe₂$ surface due to the high-affinity interaction between $WSe₂$ and A-PPG.³⁶

To further understand the interface structure relationships in the WSe₂/A-PPG composites, Raman spectroscopy was used to detect the presence of the metallic 1T phase in as-exfoliated WSe2 nanosheets at high sensitivity, as presented in Fig. 1c. The characteristics of the peak at the respective in-plane E_{2g} , out-of-plane A_{1g} , B_{2g}^1 and small peaks in the high wavenumber region differed with the 2D WSe₂ sheet thickness.^{12,16} Raman peak shifts are the major phenomenon indicative of exfoliation: as the amount of A-PPG loaded increased to 90%, the Raman peak of the $WSe₂$ nanosheets underwent a significant red-shift compared to bulk $WSe₂$, in agreement with previous reports.³⁷ The frequency difference between the 10/90 $WSe_2/A-PPG$ and WSe_2 peaks was 32.6 cm^{-1} , which corresponds to three layers or fewer – as indicated by the extracted peak shift value (Fig. 1d).³⁸ However, an increase in the intensity of the B_{2g}^1 peak provides a fingerprint of an increase in the proportion of 1T-phase Raman active modes, which are not allowed in the 2H phase,³⁹ suggesting the pristine $WSe₂$ layers stacked in 2H order $(2H-WSe₂)$ were successfully converted into 1T-phase WSe_2 (1T-WSe₂) nanosheets by incorporating A-PPG into the WSe_2 layer. Notably, in the 1T-WSe₂ Raman spectrum, the intensity of the E_{2g}^1 peak due to the remaining 2H-WSe₂ was almost overwhelmed by the signal strength of the A_{1g} peak. In contrast, the intact $2H-WSe₂$ spectrum contained a stronger E_{2g}^1 peak than A_{1g} peak as the amount of A-PPG increased.⁴⁰ In other words, as the amount of A-PPG increased, peak splitting and the intensity of the A_{1g} mode increased significantly as the content of $1T-WSe₂$ increased. The absence of the small peaks (2M modes, related to second order and combinational Raman modes) in the higher frequency region $(350-400 \text{ cm}^{-1})$ of the Raman spectrum of exfoliated $WSe₂$ further confirm formation of the high-quality, few-layer 1 T-WSe₂ phase.^{12,34,41} This result further indicates that the extent of exfoliation and proportion of the $1T-WSe₂$ phase can be controlled by systematically tuning the A-PPG content of the composites; this feature is highly desirable yet extremely rare within traditional nanocomposites and dispersing complex material systems.

In order to verify the presence of A-PPG macromers on the surface of WSe₂, X-ray diffraction (XRD) was performed at 25 °C. As shown in Fig. 2a and b, the intensity of the diffraction peak at 13.70° assigned to the (002) crystallographic plane in the XRD pattern of bulk $2H-WSe₂$ dramatically reduced as the content of A-PPG increased. In addition, a shoulder peak emerged at about 13.40 $^{\circ}$, which originates from the 1T-WSe₂ phase – as indicated by the enlarged (002) diffraction peak.⁹ After exfoliation, the intensity of the (002) reflection peak for each composite

Fig. 2 (a) XRD patterns for pure A-PPG, pure $WSe₂$ and $WSe₂/A-PPG$ composites. (b) Enlarged view of the (002) diffraction peaks for all samples. High-resolution XPS spectra of (c) W 4f for bulk WSe₂ and 50/ 50 WSe₂/A-PPG, (d) C 1s for A-PPG and 50/50 WSe₂/A-PPG.

substantially reduced and slightly shifted from 13.45° (pristine WSe_2) to 13.97° (10/90 WSe₂/A-PPG) as the A-PPG content increased from 50 to 90%, leading to simultaneous disappearance of the (006) and (008) reflection peaks at 41.5° and 56.7° , possibly due to the effect of the non-covalent interactions between $WSe₂$ and A-PPG. Therefore, three new small reflection peaks at 31.3°, 37.6° and 47.2° appeared in the XRD profiles, corresponding to the (100), (103) and (105) crystal planes (Fig. S1†), a consequence of assembly of A-PPG on the surface of WSe₂, which thus tended to form highly exfoliated WSe₂ nanosheets containing a high proportion of the metallic 1T phase.19,42 The weakening of the diffraction peaks revealed the exfoliated $WSe₂$ has low crystallinity, much weaker stacking in the c direction, no defects and small crystallite size.^{43,44} This further suggests that the introduction of A-PPG into the $WSe₂$ matrix significantly affects the phase behavior of $WSe₂$ due to the self-complementary hydrogen-bonded adenine–adenine interactions involved in the self-assembly of A-PPG.²⁰

To further confirm how these specific interactions influence the WSe₂ exfoliation process, X-ray photoelectron spectroscopy (XPS) was employed to confirm the bonding characteristics of the atomic interaction between $WSe₂$ and A-PPG. As shown in Fig. 2c, the high-resolution W 4f photoelectron spectrum of pristine WSe₂ displayed peaks at binding energies of 32.3 and 34.4 eV, corresponding to the W $4f_{7/2}$ and W $4f_{5/2}$ states, respectively,^{44,45} while lower binding energies of 27.8 for W $4f_{7/2}$ and 30.0 eV for W $4f_{5/2}$ were observed for the 50/50 WSe₂/A-PPG composite. This confirms semiconducting $2H$ -phase WSe₂ can be successfully converted into metallic 1T-phase $WSe₂$ by

incorporating A-PPG into the $WSe₂$ layer, as the binding energies shifted negatively for the W $4f_{7/2}$ and W $4f_{5/2}$ peaks after exfoliation of the layers.⁴⁶⁻⁴⁸ In addition, peak deconvolution also showed that the percentage of $1T-WSe₂$ increased to 80% compared to pristine WSe_2 (2.6%) in the bulk, consistent with the Raman analysis.^{45,49}

Fig. 2d displays the high-resolution C 1s spectra of the A-PPG and $50/50$ WSe₂/A-PPG composite deconvoluted into several individual peaks. The appearance of the C–C/C=C, C–N/C=N and C $=$ O XPS peaks in the composite at 283.5, 284.2, 284.8 and 287.5 eV, respectively, reflect the intermolecular interactions between the adenine/ester groups of A-PPG and exfoliated $WSe₂$ nanosheets. The additional C–W peak (281.2 eV), which was absent in pure A-PPG, mainly reflects the π - π stacking of the adenine unit of A-PPG and electron-rich atoms on the $WSe₂$ basal plane. Similar binding energy shifts also occurred for N 1s, O 1s and Se 3d in the $WSe₂/A-PPG$ composites compared to pristine A-PPG (Fig. S2†). The lower binding energy of the elements after exfoliation can be mainly attributed to the van der Waals interactions between the large electronegative atoms in A-PPG and electron-deficient atoms on the edge sites of WSe₂.^{5,20} In other words, the nitrogen and electron-rich structure of adenine-based supramolecular A-PPG is indeed highly attractive for induction of noncovalent interactions with $WSe₂$, including N–Se, N–W and W/Se– π – π coordination, as well as binding through charge transfer.^{4,26} Overall, the Raman, XRD and XPS results confirm that incorporation of A-PPG further induced a phase transition from the semiconductor $2H-WSe₂$ to metallic 1 T-WS e_2 and a microstructural transition from crystal layered structures to exfoliated nanosheets.

Further validation of the microstructures and morphologies of pristine $WSe₂$ and the functionalized composites was performed by scanning electron microscopy (SEM) and highresolution transmission electron microscopy (HRTEM). Fig. 3 shows the SEM micrographs of pristine A-PPG and WSe, in comparison with their exfoliated counterparts. Highmagnification SEM (Fig. 3e) revealed A-PPG can self-assemble into a micellar-like morphology with an average diameter of ca. 14 nm, in agreement with the dynamic light-scattering results (Fig. S3a†).^{20,50} This suggests the A-PPG chains are able to form large aggregates in polar THF solution, and form supramolecular micelles via the intermolecular hydrogen bonding interaction between adenine–adenine moieties. In the bulk state, the flat and smooth surface of stack-layered pristine $WSe₂$ is clearly visible in Fig. 3a and c, along with the polygonal edge arrangements and thicknesses in the few micrometerrange.^{13,45} In contrast, the 50/50 WSe₂/A-PPG composite exhibited a disordered morphology of folding $WSe₂$ nanosheets, with a lateral size of $5-10 \mu m$ (Fig. 3b), indicating A-PPG acts as an effective dispersant to prevent reaggregation and restacking of the $WSe₂$ nanosheets. Surprisingly, high-magnification SEM image (Fig. 3d) revealed the self-assembled micelles of A-PPG could self-assemble to form highly clustered structures and adsorbed on the surface of the exfoliated $WSe₂$ sheets, which was diametrically opposite to the smooth surface of bare $WSe₂$ (Fig. 3c). These observations indicate that A-PPG has a high binding affinity for WSe_2 nanosheets due to the strong specific

Fig. 3 SEM images of (a, c) pristine WSe₂, (b, d) exfoliated 50/50 WSe₂/ A-PPG composite and (e) pristine A-PPG. (f) Schematic diagram illustrating the interaction between spherical micelles and $WSe₂$ nanosheets.

interactions and is stably adsorbed onto the $WSe₂$ surface $(Fig. 3f).$ ⁵¹⁻⁵³

Self-assembly of the adenine units in A-PPG played a significant role in the construction of the highly ordered hierarchical microstructure on the surface of $WSe₂$ nanosheets. Thus, HRTEM was performed at 25 $^{\circ}$ C under high vacuum to further observe the self-assembled nanostructures of A-PPG in the 50/ 50 WSe₂/A-PPG composite. As shown in Fig. 4, pristine WSe₂ microstructures were distributed as irregular flakes with a high density of crystal surfaces. In addition, the two-dimensional fast Fourier transform (FFT) pattern in the inset of Fig. 4a illustrates the ordered crystalline structure of $WSe₂$ with a 0.32 nm lattice distance.4,16 We carefully examined the structures from randomly selected areas of a $WSe₂$ crystal sheet (in the green and red squares of Fig. 4b) and confirmed the coexistence of hexagonal structures, which are typically seen in the 1T phase, and also honeycomb lattices, characteristic of the 2H phase (Fig. 4c and d).29,54 These results were consistent with the XPS and Raman data. In the $50/50$ WSe₂/A-PPG composite, selfassembly of A-PPG into contracted and extended lamellar microstructures on the surface of exfoliated $WSe₂$ nanosheets was clearly observed (Fig. 5c, labelled as 'I' and 'II' respectively), with a contracted lamellar d-spacing of 1.0 nm and an extended lamellar d-spacing of 1.8 nm. In addition, the two-dimensional FFT pattern in the right upper corner of Fig. 5a shows a disordered crystal structure with a 0.26 nm lattice distance, which could be attributed to adsorption of the lamellar microstructure of A-PPG over the surface of $WSe₂ via a "specific interaction"$

Fig. 4 (a) HRTEM image of pristine WSe₂ and the corresponding electron diffraction pattern (insert). (b) Enlarged view of (a) showing the surface morphology of WSe 2 . The squares indicate 1T-WSe 2 (green) and 2H–WSe₂ (red) crystalline structures, which are shown in detail in (c) and (d), respectively.

between the polar moieties of A-PPG and the surface of the WSe_2 nanosheets (Fig. 5b).

Most notably, the d-spacing values of the contracted and extended lamellar microstructures, approximately 1.0 nm and 1.8 nm respectively, were significantly different to the theoretical PPG chain length (1.33 nm),²⁰ possibly due to coexistence of the 1T-WSe₂ and 2H-WSe₂ phases that possess different physical properties and may contribute to dynamic contraction/ extension-motion in the flexible PPG backbone during the self-assembly process. Thus, the interlamellar distance of the lamellar structure and transition mechanisms of A-PPG can be reasonably explained by a theory of chain contraction/extension transition within the flexible polymer.⁵⁵ However, the 1Tstructure is comprised of a negatively charged ion^{8,56} that possesses superior electrical conductivity and catalytic activity (compared to the 2H phase) and has shown enhanced performance in electrocatalytic hydrogen evolution⁵¹ and supercapacitors.22,23 Therefore, the electron-rich 1T phase in the surface of exfoliated $WSe₂$ nanosheets ('II' region of Fig. 5c) may trigger formation of an extended PPG backbone and thus significantly increase lamellar d -spacing by electron transfer to A-PPG compared to the surface of $2H-WSe₂$ phase.^{29,57} The unique $1T-WSe₂/A-PPG$ architecture maximizes the interfacial atomic contact between metallic $1T-WSe₂$ and A-PPG. $1T-WSe₂$ enhances the electron density of nitrogen donor atoms in the adenine units via a resonance effect to promote a stable interaction between A-PPG adenine moieties and $WSe₂$, resulting in stretching of the A-PPG linear chain and an increase in interlamellar distance.^{54,56} The chemically stable $2H-WSe₂$ phase in the surface of exfoliated WSe_2 nanosheets ('I' region of Fig. 5c)

Fig. 5 (a) HRTEM image of $50/50$ WSe₂/A-PPG composite and the corresponding electron diffraction pattern (given as insert). (b) Schematic illustrating the specific interaction between A-PPG and WSe2 nanosheets. (c) Enlarged view of (a) showing the contracted and extended lamellar microstructure of A-PPG on the surface of WSe₂. (d) HRTEM image of the region enclosed by the white square in panel (c). (e) SAXS data for A-PPG and 50/50 WSe₂/A-PPG recorded at 25 °C.

may have an insignificant effect on extension of the A-PPG polymer segment. However, the 2H-WSe₂ phase may enable more contraction of the flexible PPG backbone compared to the theoretical d-spacing value (1.33 nm) of free A-PPG due to possible weakening of intermolecular interactions between WSe₂ and A-PPG leading to a more thermodynamically stable A-PPG structure. Based on the above findings and description, we reasonably conjecture that coexistence of the 2H and 1T phases trigger the self-assembly of A-PPG into contracted and extended lamellar morphologies, respectively. Contraction and extension of the interlamellar distance in the PPG backbone could be easily tuned by regulating the controllable hydrogen-bonded structure between adenine units, which depends on the surface reactivity of the heterogeneous phase structure of $WSe₂$.

In order further to confirm the d -spacing values of the adsorbed contracted and extended lamellar microstructures of A-PPG on the WSe_2 surface, small-angle X-ray scattering (SAXS) measurements were used to identify the lamellar crystalline phases associated with A-PPG in pure A-PPG and the 50/50 $WSe₂/A-PPG$ composite. As shown in Fig. 5f, the SAXS profile of 50/50 WSe₂/A-PPG composite at 25 °C exhibited two scattering peaks at $q = 5.0$ nm⁻¹ (d = 1.26 nm) and $q = 3.7$ nm⁻¹ (d) $=$ 1.70 nm). The peak at $q = 5.0$ nm⁻¹ may be attributed to a decrease in lamellar d-spacing of the linear A-PPG polymer due to the inactive surface of the $2H-WSe₂$ phase, resulting in formation of a slightly contracted lamellar microstructure on the 2H–WSe₂ surface. The other scattering peak located at $q =$ 3.7 nm^{-1} , with significantly longer *d*-spacing than that of pristine A-PPG (1.33 nm), is possibly attributed to the highly reactive surface of 1T-phase WSe₂,⁵⁵ which enhances chain extension of the flexible PPG backbone. In addition, the SAXS results showed similar trends as the HRTEM images (Fig. 5c). The HRTEM observations also revealed $1T-WSe₂$ and A-PPG interact via an effective noncovalent interaction, with each interacting junction contributing partial π bonds and charges to form a stable charge-transfer complex at the interface between WSe_2 and A-PPG.^{4,26} On the other hand, the contractile and extended lamellar structures may help to stabilize the modified chemical structure and prevent degradation of $WSe₂$ and increase charge transport across the interface.^{22,23}

Generally, when $WSe₂$ nanosheets were highly covalently functionalized with A-PPG, their surfaces were absorbed by randomly distributed domains of well-ordered lamellar or micelle A-PPG microstructures, which prevented restacking of the exfoliated $WSe₂$ nanosheets and also improved their structural stability (Scheme 2). Mechanistically, we realize the adenine moieties of A-PPG are an essential unit that has the affinity to self-assemble spontaneously into desirable microstructures on the WSe $₂$ surface, primarily due to the presence of</sub> the favorable hydrogen bonding interaction between selfcomplementary adenine moieties. When A-PPG is present in excess in the composites, at the beginning of the blending

Scheme 2 Proposed exfoliation processes for adsorption of (a) selfassembled structures, (b) contracted/extended lamellar microstructures and (c) micellar aggregates of A-PPG on the surface of exfoliated $WSe₂$ nanosheets.

Chemical Science Edge Article

process, A-PPG tends to generate a well-defined lamellar structure with excellent long-range order due to the low concentration of A-PPG on the surface of $WSe₂$ (Scheme 2a). Subsequently, excess A-PPG forms a large number of micellar aggregates over the flat surface of the lamellar hierarchical structures (Scheme 2c). Due to the presence of both the 1T and 2H phases in the WSe2 nanosheets, A-PPG not only drives the transition between contractile and extended lamellar structures, but also effectively manipulates the intermolecular d -spacing of the lamellar microstructure on the surfaces of the exfoliated 1 T-WSe₂ and $2H-WSe₂$ phases (Scheme 2b). Collectively, this study demonstrates that contraction and extension of the lamellar microstructure depend on the hydrogen bond motion of adenine dimers, interfacial affinity between $WSe₂$ and A-PPG, and the different surface activity of the $WSe₂$ phases. In addition, tuning the content of A-PPG in the composite can easily control the extent of $WSe₂$ exfoliation and enables manipulation of the formation of lamellar structures or micellar aggregates over the surface of WSe₂ via noncovalent polymerization of A-PPG.⁵⁵ Therefore, this new discovery suggests the self-assembly behavior of A-PPG can be employed to effectively tune the intrinsic physical properties of inorganic 2D nanomaterials and related heterostructures without additional chemical treatments.

In order to determine the number of $WSe₂$ layers in the composites, atomic force microscopy (AFM) was performed to measure the step height of exfoliated $WSe₂$ nanosheets on a silicon substrate. The theoretical $WSe₂$ monolayer thickness is 0.64 nm.¹² The measured step height of $50/50$ WSe₂/A-PPG layer was 3.0–3.5 nm (line scan in Fig. S4†), corresponding to fewer than five layers of WSe_2 nanosheets, with a lateral dimension of 0.2-2 μ m, consistent with the DLS results (Fig. S3b†). In addition, the edges of $WSe₂$ had higher heights than the central structures; this may be due to the edges being either wrinkled or the formation of micelle-like or long-range ordered lamellar structures of A-PPG over the surface of $WSe₂$ due to the noncovalent specific interaction between WSe_2 and A-PPG.^{7,20,58,59} Differential scanning calorimetry (DSC) and variabletemperature Fourier transform infrared (VT-FTIR) spectroscopy were also employed to investigate thermoreversible stability and phase transition behavior within the $WSe₂/A-PPG$ system. The DSC and VT-FTIR (Fig. $S5-S7\dagger$) showed the WSe₂/ A-PPG composites appeared to undergo a thermoreversible transition between ordered crystals and disordered fluids, and the hydrogen-bonded supramolecular interactions between adenine moieties reverted back perfectly to the original state as the samples were slowly cooled from 120 $^{\circ}{\rm C}$ to 25 $^{\circ}{\rm C,}$ as a result of the relationship between the thermoreversible hydrogen bond interactions and phase transition behavior. (The DSC and VT-FTIR are described in more detail in the ESI†). Furthermore, thermogravimetric analysis (TGA) (Fig. S8[†]) confirmed the WSe2/A-PPG composites possess excellent thermal stability due to the presence of the exfoliated $WSe₂$ nanosheets in the matrix phase, which indicates the potential to achieve temperatureresponsive functional composites with higher thermal stability.⁶⁰ Based on results obtained in this study, the physical properties of $WSe_2/A-PPG$ composites - in particular their

contracted/extended lamellar microstructures and thermoresponsive behavior (compared to pristine $WSe₂$) – are highly suitable for potential applications in solution-processed photoluminescent sensors and semiconductor devices.^{61,62}

Conclusions

We have designed a new, simple, effective exfoliation method using A-PPG macromer as a dispersant and stabilizer to produce exfoliated 2D WSe $_2$ nanosheets in organic solution. Spectroscopic, compositional and morphological studies confirmed formation of micelle-like and lamellar structures of highly adsorbed A-PPG on the surface of $WSe₂$ due to the specific noncovalent interaction between A-PPG and the $WSe₂$ nanosheets. Moreover, the electron-rich metallic 1T-WSe₂ phase may trigger the self-assembly of A-PPG resulting in formation of an extended lamellar microstructure by increasing the electron density of the nitrogen donor atoms in the adenine unit via a resonance effect, which enhanced the structural stability of exfoliated WSe₂ through 1T-WSe₂/A-PPG interactions. In contrast, the chemically stable semiconductor $2H-WSe₂$ phase assisted the formation of a contracted lamellar A-PPG microstructure due to weakening of the intermolecular interactions between $2H-WSe₂$ and A-PPG. Tuning the A-PPG content of the composites can be used to control the layer thickness of the exfoliated $WSe₂$ nanosheets and physical and chemical properties of $WSe₂$ in order to obtain nanocomposites with the desired functional characteristics. In addition, these newlydeveloped composites exhibit unique liquid–solid phase transition behavior and excellent thermoreversible properties due to the presence of the highly stable, reversible hydrogen-bonded adenine network in the composites. To the best of our knowledge, this $WSe₂/A-PPG$ system is the first method to exploit A-PPG macromers to produce highly exfoliated $WSe₂$ and enable controlled, self-assembly of multifunctional supramolecular polymer structures on the surface of $WSe₂$. This strategy may provide a useful conceptual framework for further developing and extending the applications of $WSe₂$ -based nanocomposites in solution-processed temperature-switching semiconductor devices. Openical Science

Theorem Access APPG tends on generate a well-defined lamelar name. To more than the common
second of the common access APPG tends of the common access Article is the common and tends of the common and te

Experimental section

All chemical materials, characterizations and instrumentation used in this work are described in the ESI.†

Synthesis of adenine end-capped PPG (A-PPG)

A-PPG was produced from low molecular weight PPG diacrylate (average molecular weight ~ 800 , ca. 14 repeat units) and adenine via Michael addition reaction using potassium tertbutoxide as an initiator. The synthesis procedure is described in detail in our previous work.^{20,28}

Preparation of bulk tungsten diselenide $(WSe₂)$

WSe₂ single crystals were grown by chemical vapor transport.²⁹ This method contains two steps. First, prior to crystal growth,

a powdered mixture of the pure starting material was prepared (W: 99.99% pure and Se: 99.999%) by reaction at 1050 °C for 10 days in evacuated quartz ampules. To improve the stoichiometry, 2 mol% excess selenium was added with respect to the stoichiometric mixture of the constituent elements. About 10 g of this mixture was placed into a quartz ampule (22 mm OD, 17 mm ID, 20 cm length), which was then evacuated to a pressure of 10^{-6} Torr and sealed. The mixture was slowly heated to 1050 °C. In the second step, chemical transport was achieved by mixing an appropriate amount of material and transport agent $(I_2$ at 12 mg cm $^{-3}$), which was placed in a quartz tube (22 mm OD, 17 mm ID, 20 cm length), cooled with liquid nitrogen, evacuated to 10^{-6} Torr and sealed. The growth temperature was set from 1050 to 960 °C with a gradient of -4.5 °C cm⁻¹ (with crystal growth occurring in the cooler section). The reaction was maintained for 480 h, producing large single crystals with mirror-like surfaces. Edge Article

2018 Article is the common access Article is licensed to the 100 λ May 2028. The Mondmatical Creative Common Access Article is licensed under the component and the Creative Common Street is licensed under

Preparation of $WSe₂/A-PPG$ composites

WSe2/A-PPG composites were produced by the sonicationassisted liquid exfoliation method. A-PPG was added into the THF and stirred at room temperature until PPG completely dissolved. Choosing a moderate polar THF for preparing composite materials can possibly be used to maintain the hydrogen-bonded structures of A-PPG in solution.^{20,27} Various contents of $WSe₂$ were added to the same solution and sonicated for 1 h at 25 \degree C to produce stable, homogenous dispersions of WSe₂/A-PPG. The synthesized impregnated WSe₂/A-PPG composites were dark brown, and were dried completely by removing the solvent and volatile impurities in a vacuum oven at 60 °C. For comparison, pristine $WSe₂$ and A-PPG samples were prepared under the same conditions.

Conflicts of interest

The authors declare no conflicts of interest in this article.

Acknowledgements

This study was supported financially by the Ministry of Science and Technology, Taiwan, under contracts MOST 104-2221-E-011-153 and MOST 105-2628-E-011-006-MY2.

Notes and references

- 1 M.-Y. Tsai, A. Tarasov, Z. R. Hesabi, H. Taghinejad, P. M. Campbell, C. A. Joiner, A. Adibi and E. M. Vogel, ACS Appl. Mater. Interfaces, 2015, 7, 12850–12855.
- 2 C. A. Joiner, P. M. Campbell, A. A. Tarasov, B. R. Beatty, C. J. Perini, M.-Y. Tsai, W. J. Ready and E. M. Vogel, ACS Appl. Mater. Interfaces, 2016, 8, 8702–8709.
- 3 A. Pant, Z. Mutlu, D. Wickramaratne, H. Cai, R. K. Lake, C. Ozkan and S. Tongay, Nanoscale, 2016, 8, 3870–3887.
- 4 B. Liu, Y. Ma, A. Zhang, L. Chen, A. N. Abbas, Y. Liu, C. Shen, H. Wan and C. Zhou, ACS Nano, 2016, 10, 5153–5160.
- 5 C. Lu, Y. Liu, Y. Ying and J. Liu, Langmuir, 2017, 33, 630–637.
- 6 H. Taghinejad, M. Taghinejad, A. Tarasov, M.-Y. Tsai, A. H. Hosseinnia, H. Moradinejad, P. M. Campbell, A. A. Eftekhar, E. M. Vogel and A. Adibi, ACS Photonics, 2016, 3, 700–707.
- 7 D. Jariwala, A. R. Davoyan, G. Tagliabue, M. C. Sherrott, J. Wong and H. A. Atwater, Nano Lett., 2016, 16, 5482–5487.
- 8 B. Mahler, V. Hoepfner, K. Liao and G. A. Ozin, J. Am. Chem. Soc., 2014, 136, 14121–14127.
- 9 Z. Liu, H. Zhao, N. Li, Y. Zhang, X. Zhang and Y. Du, Inorg. Chem. Front., 2016, 3, 313–319.
- 10 M. Zou, J. Chen, L. Xiao, H. Zhu, T. Yang, M. Zhang and M. Du, J. Mater. Chem. A, 2015, 3, 18090–18097.
- 11 D. Akinwande, N. Petrone and J. Hone, Nat. Commun., 2014, 5, 5678.
- 12 H. Zhou, C. Wang, J. C. Shaw, R. Cheng, Y. Chen, X. Huang, Y. Liu, N. O. Weiss, Z. Lin, Y. Huang and X. Duan, Nano Lett., 2015, 15, 709–713.
- 13 H. Li, Z. Peng, J. Qian, M. Wang, C. Wang and X. Fu, ACS Appl. Mater. Interfaces, 2017, 9, 28704–28715.
- 14 L. Ci, L. Song, C. Jin, D. Jariwala, D. Wu, Y. Li, A. Srivastava, Z. F. Wang, K. Storr, L. Balicas, F. Liu and P. M. Ajayan, Nat. Mater., 2010, 9, 430–435.
- 15 P. Cheng, K. Sun and Y. H. Hu, Nano Lett., 2016, 16, 572–576.
- 16 M. Z. M. Nasir, C. C. Mayorga-Martinez, Z. Sofer and M. Pumera, ACS Nano, 2017, 11, 5774–5784.
- 17 X. Yu and K. Sivula, Chem. Mater., 2017, 29, 6863–6875.
- 18 C. Tan, X. Cao, X.-J. Wu, Q. He, J. Yang, X. Zhang, J. Chen, W. Zhao, S. Han, G.-H. Nam, M. Sindoro and H. Zhang, Chem. Rev., 2017, 117, 6225–6331.
- 19 M.-Y. Tsai, S. Zhang, P. M. Campbell, R. R. Dasari, X. Ba, A. Tarasov, S. Graham, S. Barlow, S. R. Marder and E. M. Vogel, Chem. Mater., 2017, 29, 7296–7304.
- 20 A. A. Muhabie, C. C. Cheng, J. J. Huang, Z. S. Liao, S. Y. Huang, C. W. Chiu and D. J. Lee, Chem. Mater., 2017, 29, 8513–8520.
- 21 G. Z. Magda, J. Pető, G. Dobrik, C. Hwang, L. P. Biró and L. Tapasztó, Sci. Rep., 2015, 5, 14714.
- 22 G. Eda, T. Fujita, H. Yamaguchi, D. Voiry, M. Chen and M. Chhowalla, ACS Nano, 2012, 6, 7311–7317.
- 23 J. Brivio, D. T. L. Alexander and A. Kis, Nano Lett., 2011, 11, 5148–5153.
- 24 F. Huang and O. A. Scherman, Chem. Soc. Rev., 2012, 41, 5879–5880.
- 25 P. Wei, X. Yan and F. Huang, Chem. Soc. Rev., 2015, 44, 815– 832.
- 26 R. C. Selhorst, E. Puodziukynaite, J. A. Dewey, P. Wang, M. D. Barnes, A. Ramasubramaniam and T. Emrick, Chem. Sci., 2016, 7, 4698–4705.
- 27 C. C. Cheng, F. C. Chang, J. H. Wang, J. K. Chen, Y. C. Yen and D. J. Lee, Nanoscale, 2016, 8, 723–728.
- 28 C. C. Cheng, J. J. Huang, A. A. Muhable, Z. S. Liao, S. Y. Huang, S. C. Lee, C. W. Chiu and D. J. Lee, Polym. Chem., 2017, 8, 2292–2298.
- 29 C. H. Ho, W. H. Chen, K. K. Tiong, K. Y. Lee, A. Gloter, A. Zobelli, O. Stephan and L. H. G. Tizei, ACS Nano, 2017, 11, 11162–11168.
- 30 Y. Lin, T. V. Williams and J. W. Connell, J. Phys. Chem. Lett., 2010, 1, 277–283.
- 31 R. Coehoorn, C. Haas and R. A. de Groot, Phys. Rev. B: Condens. Matter Mater. Phys., 1987, 35, 6203–6206.
- 32 A. R. Beal, J. C. Knights and W. Y. Liang, J. Phys. C: Solid State Phys., 1972, 5, 3540–3551.
- 33 W. Zhao, Z. Ghorannevis, L. Chu, M. Toh, C. Kloc, P.-H. Tan and G. Eda, ACS Nano, 2013, 7, 791–797.
- 34 W. Zhao, Z. Ghorannevis, K. K. Amara, J. R. Pang, M. Toh, X. Zhang, C. Kloc, P. H. Tan and G. Eda, Nanoscale, 2013, 5, 9677–9683.
- 35 G. S. Bang, S. Cho, N. Son, G. W. Shim, B.-K. Cho and S.-Y. Choi, ACS Appl. Mater. Interfaces, 2016, 8, 1943–1950.
- 36 J. Gu, X. Yang, Z. Lv, N. Li, C. Liang and Q. Zhang, Int. J. Heat Mass Transfer, 2016, 92, 15–22.
- 37 X. Wang, X. Chen, Y. Zhou, C. Park, C. An, Y. Zhou, R. Zhang, C. Gu, W. Yang and Z. Yang, Sci. Rep., 2017, 7, 46694.
- 38 D.-H. Kang, J. Shim, S. K. Jang, J. Jeon, M. H. Jeon, G. Y. Yeom, W.-S. Jung, Y. H. Jang, S. Lee and J.-H. Park, ACS Nano, 2015, 9, 1099–1107.
- 39 X. Luo, Y. Zhao, J. Zhang, M. Toh, C. Kloc, Q. Xiong and S. Y. Quek, Phys. Rev. B: Condens. Matter Mater. Phys., 2013, 88, 195313.
- 40 Y. Ma, B. Liu, A. Zhang, L. Chen, M. Fathi, C. Shen, A. N. Abbas, M. Ge, M. Mecklenburg and C. Zhou, ACS Nano, 2015, 9, 7383–7391.
- 41 A. Berkdemir, H. R. Gutiérrez, A. R. Botello-Méndez, N. Perea-López, A. L. Elías, C.-I. Chia, B. Wang, V. H. Crespi, F. López-Urías, J.-C. Charlier, H. Terrones and M. Terrones, Sci. Rep., 2013, 3, 1755. Openical Science

30 Y. Lin, T. V. Williams and J. W. Commol, J. Phys. Chem, Rev. 8: 30 Na, J. A. This article. Published on 2018. Also, 1975. Also, 1
	- 42 W. Zhu, X. Gao, Q. Li, H. Li, Y. Chao, M. Li, S. M. Mahurin, H. Li, H. Zhu and S. Dai, Angew. Chem., Int. Ed., 2016, 55, 10766–10770.
	- 43 P. D. Antunez, D. H. Webber and R. L. Brutchey, Chem. Mater., 2013, 25, 2385–2387.
	- 44 M. Zou, J. Zhang, H. Zhu, M. Du, Q. Wang, M. Zhang and X. Zhang, J. Mater. Chem. A, 2015, 3, 12149–12153.
	- 45 A. Y. S. Eng, A. Ambrosi, Z. Sofer, P. Šimek and M. Pumera, ACS Nano, 2014, 8, 12185–12198.
	- 46 D. Voiry, M. Salehi, R. Silva, T. Fujita, M. Chen, T. Asefa, V. B. Shenoy, G. Eda and M. Chhowalla, Nano Lett., 2013, 13, 6222–6227.
- 47 M. A. Lukowski, A. S. Daniel, F. Meng, A. Forticaux, L. Li and S. Jin, J. Am. Chem. Soc., 2013, 135, 10274–10277.
- 48 Y.-C. Lin, D. O. Dumcenco, Y.-S. Huang and K. Suenaga, Nat. Nanotechnol., 2014, 9, 391–396.
- 49 A. Anto Jeffery, C. Nethravathi and M. Rajamathi, J. Phys. Chem. C, 2014, 118, 1386–1396.
- 50 B. T. Gebeyehu, S.-Y. Huang, A. W. Lee, J. K. Chen, J. Y. Lai, D. J. Lee and C. C. Cheng, Macromolecules, 2018, 51, 1189– 1197.
- 51 D. A. Henckel, O. Lenz and B. M. Cossairt, ACS Catal., 2017, 7, 2815–2820.
- 52 X. Wang, Y. Chen, B. Zheng, F. Qi, J. He, P. Li and W. Zhang, Electrochim. Acta, 2016, 222, 1293–1299.
- 53 T. Morishita and H. Okamoto, ACS Appl. Mater. Interfaces, 2016, 8, 27064–27073.
- 54 A. Ambrosi, Z. Sofer and M. Pumera, Chem. Commun., 2015, 51, 8450–8453.
- 55 C. C. Cheng, J. H. Wang, W. T. Chuang, Z. S. Liao, J. J. Huang, S. Y. Huang, W. L. Fan and D. J. Lee, Polym. Chem., 2017, 8, 3294–3299.
- 56 C. Zhao, J. M. Ang, Z. Liu and X. Lu, Chem. Eng. J., 2017, 330, 462–469.
- 57 S. S. Chou, N. Sai, P. Lu, E. N. Coker, S. Liu, K. Artyushkova, T. S. Luk, B. Kaehr and C. J. Brinker, Nat. Commun., 2015, 6, 8311.
- 58 Y. Liu, C. Tan, H. Chou, A. Nayak, D. Wu, R. Ghosh, H.-Y. Chang, Y. Hao, X. Wang, J.-S. Kim, R. Piner, R. S. Ruoff, D. Akinwande and K. Lai, Nano Lett., 2015, 15, 4979–4984.
- 59 W. Zhang, Y. Cao, P. Tian, F. Guo, Y. Tian, W. Zheng, X. Ji and J. Liu, ACS Appl. Mater. Interfaces, 2016, 8, 32440–32449.
- 60 R. M. Silverstein, G. C. Bassler and T. C. Morrill, Spectrometric Identification of Organic Compounds, John Wiley & Sons, NewYork, 1991.
- 61 H. Li, G. Lu, Y. L. Wang, Z. Y. Yin, C. X. Cong, Q. Y. He, L. Wang, F. Ding, T. Yu and H. Zhang, Small, 2013, 9, 1974–1981.
- 62 H. Li, J. Wu, Z. Yin and H. Zhang, Acc. Chem. Res., 2014, 47, 1067–1075.