RSC Advances



View Article Online

View Journal | View Issue

PAPER

Check for updates

Cite this: RSC Adv., 2019, 9, 28857

Experimental investigation of shale oil recovery from Qianjiang core samples by the CO₂ huff-npuff EOR method

Lei Li, ^[]^{ab} Chengwei Wang,^{ab} Dongsheng Li,^{ab} Jingang Fu,^{ab} Yuliang Su^{*ab} and Yuting Ly

CO₂ Huff-n-Puff (HnP) is an effective technique for enhancing oil recovery (EOR) that can be applied to shale oil reservoirs faced with poor natural productivity and low water injectivity. The main objective of this study is to investigate the interactions of CO₂ and formation crude oil, and evaluate the CO₂ HnP performance in shale oil reservoirs in the Qianjiang depression in China. In this study, the variation rules of oil phase behavior, viscosity, saturation pressure, and swelling factor at different CO₂ contents of 0 to 65% were studied. A series of HnP experiments were conducted. The factors affecting the oil recovery were discussed, and Nuclear Magnetic Resonance (NMR) tests were conducted on core samples at different stages of the HnP process. The results show that the injected CO₂ can make an positive change in the crude oil phase behavior. The oil-gas two-phase region enlarges and the saturation pressure increases as more CO_2 is dissolved in the formation oil, which is beneficial to oil production. The dissolution of CO₂ in the oil phase increased the oil swelling degree by 1.492 times, and the viscosity decreased from 1.944 to 0.453 mPa s. The HnP experimental results demonstrate that the soaking time should be determined based on the injection pressure. Miscible conditions is a viable option for CO_2 HnP as 10% more oil can be produced using miscible HnP and save more than half of the soaking time. The results illustrate that fracture is the most important factor affecting oil recovery, and the performance of HnP EOR on core samples with fractures is almost 25% better than those without fractures. However, the core matrix permeability has an almost negligible effect on the performance of CO₂ HnP. The NMR tests show that the oil recovered in the first cycle was dominated by macropores and mesopores, followed by small pores. In the latter HnP cycles, the oil in small pores and micropores becomes the main oil-producing area. This study may provide a better understanding of the CO₂ HnP enhanced recovery strategy for shale reservoirs.

Received 12th July 2019 Accepted 9th September 2019 DOI: 10.1039/c9ra05347f

rsc.li/rsc-advances

Introduction 1.

 CO_2 is safe, reliable, and has a wide range of sources, and is the most promising gas source for enhanced oil recovery technology.1-4 CO2 has good solubility in crude oil, and the solubility of CO₂ increases with the increase of pressure.^{5,6} Under reservoir conditions, CO₂ can dissolve in crude oil, expanding crude oil volume, reducing the oil viscosity and oil-gas interfacial tension, and increasing crude oil mobility.^{7,8} All these mechanisms provide favorable conditions for crude oil production.9 At the same time, CO_2 is a common greenhouse gas. The public

has paid more and more attention to the greenhouse effect nowadays. In addition to studying CO2 emissions reduction, the way to make effective use of CO₂ also becomes a research hotspot.^{10,11} CO₂ injection technology can effectively develop lowpermeability oil and gas resources. Meanwhile, it can alleviate the greenhouse effect to a certain extent.12 There are two types of CO2 injection which are CO2 flooding and CO2 huff-n-puff (HnP). During the CO_2 flooding mode, CO_2 is injected through one injection well, and oil and gas will be produced from one production well. In the hydraulic fractured shale reservoirs, the injected CO₂ will break through from the injection well to the production well along the fractures or high permeability channels in reservoirs. Whereas, CO₂ HnP uses one well as both injection well and production well to avoid gas break through. There are three stages during this process: gas injection stage, well soaking stage, and production stage. After the process, the oil under the control of the well will be produced.13,14 Three main characteristics make CO2 HnP an efficient and feasible EOR technology. First, it's economically

This article is licensed under a Creative Commons Attribution-NonCommercial 3.0 Unported Licence. Open Access Article. Published on 13 September 2019. Downloaded on 8/9/2025 9:39:13 AM

[&]quot;Key Laboratory of Unconventional Oil & Gas Development (China University of Petroleum (East China)), Ministry of Education, Qingdao, China. E-mail: suyuliang@upc.edu.cn; Tel: +86-15224450387

^bSchool of Petroleum Engineering, China University of Petroleum (East China), Qingdao, China

^cCollege of Mechanical and Electronic Engineering, Shandong University of Science and Technology, Qingdao, China

RSC Advances

feasible and relatively easier to inject CO₂ to shale reservoirs to keep the reservoir pressure high as compared to most of the other high viscosity injection fluids such as water or polymer.¹⁵ With high injectivity, the oil swept volume improved, resulting in more residual oil that can be driven.¹⁶ Second, the injected CO₂ improved oil displacement efficiency by dissolving into the shale oil and influencing the oil/gas phase equilibrium during the soaking period. Third, during the production stage, a dissolved gas drive is formed when pressure drops. Combined with the function of oil-gas interfacial tension reduction, more oil can be produced.^{17,18} The HnP schedule such as the work time for the three stages or the gas injection rate and injection pressure can be adjusted based on the properties of reservoirs. Thus, CO₂ HnP has the advantages of strong pertinence, short cycle, and fast capital recovery.¹⁹

CO₂ HnP was first applied in heavy oil production. In the mid-1960s in China, the laboratory experiments were conducted in Daqing and Shengli Oilfields, respectively. In the mid-1990s, Daqing oilfield, Jiangsu oilfield, Jilin oilfield, Zhongyuan oilfield in China all carried out some pilot tests.^{20,21} However, the development progress of this technology is relatively slow due to the shortage of CO₂ resources and the prominent gas channeling contradiction in China. In the United States, the CO₂ HnP test was carried out in light oil reservoirs. Bretagne (1985) successfully conducted the CO2 HnP test in Shoemaker Oilfield in shallow light-oil-depleted reservoirs.²² Their results showed that crude oil production was increased by 2-3 times, and the water content was reduced by more than 90%. Monger et al. (1988) conducted 14 field tests and combined them with laboratory experiments to study the stimulation effect of CO₂ in light oil reservoirs.²³ They proved that CO₂ could increase the residual oil production after water flooding. Since 1990, the United States Appalachian Basin started CO₂ HnP production, which lasted for 5 years, and implemented a total of 390 HnP operations in 240 wells, with a total oil increase of 12 476 t.24 It is concluded that the change of water/oil relative permeability by CO₂ HnP is the main mechanism of the reservoir stimulation. Torabi and Asghari (2010) conducted a laboratory study to examine the performance and efficiency of CO₂ HnP in light-oil fractured porous media.25 The results showed that CO2 HnP technology significantly improved the recovery, and it recovered more than 95% of the oil from the fracture-matrix experimental model saturated with normal decane when the CO₂ HnP was conducted at 13.34 MPa. They also announced that the effect of core permeability was less pronounced when CO2 was injection at miscible conditions.

Recent years, CO_2 HnP method has been applied to enhance unconventional oil recovery in light oil and tight reservoirs.²⁶⁻²⁸ Song *et al.* (2013) compared water and CO_2 injection experiments on cores of Bakken tight formation, and obtained that the degree of CO_2 recovery under near-miscible and miscible conditions was higher than that under water flooding.²⁹ Gamadi *et al.* (2014) did experiments to study the cyclic CO_2 injection in shale oil EOR using mineral oil and cores from Mancos and Eagle Ford.³⁰ The laboratory results indicated that cyclic CO_2 injection improved recovery of shale oil cores from 33% to 85% depending on the shale core type and the other operating

parameters. Li and Sheng measured the efficiency of shale oil recovery through laboratory experiments and numerical simulation of using methane HnP.31 Yu et al. (2016) further explored the influences of soaking time and consumption time on fracture-matrix shale reservoirs in huff and puff experiments using N2.32 Li et al. (2019) conducted experiments comparing the effect of N2 and CO2 on EOR performance, verifying the great potential of CO₂ in improving shale oil recovery.³³ Other researchers use commercial software such as CMG and Eclipse to simulate the process of CO2 HnP, and investigated the influences of parameters including pressure, injection rate, gas diffusivity, soaking time, and fractures on the efficiency of HnP EOR.34-41 Sheng (2017) reviewed and discussed previous experiments and simulations on gas injection recovery in shale reservoirs.42 He concludes that gas injection in shale reservoirs is more practical and effective than other EOR methods. The simulation results reflect the CO₂ HnP performance to some extent. However, the simulation method includes lots of assumption, which cannot represent the real core characteristics, such as core heterogeneity, pore size distribution, organic matter properties, and so on. Experiment work on core scale samples have indicated the great potential of CO₂ HnP in the recovery of shale oil. However, it is seen that core samples used in the experiments are purely matrix without presence of natural fractures. The experiments of core samples with presence of natural fractures will be more practical significance to evaluate oil production potential from shales. Also, in all the above study, the oil properties changes such as oil swelling properties, phase behavior due to the addition of CO2 are not well discussed. The underlying mechanisms of CO2 HnP cannot be well understood without the analysis of the reaction of CO₂ and the target shale oil.

At present, the application of CO₂ huff-n-puff technology in shale reservoir is still in the stage of laboratory research and field test. This technology has many advantages than other kinds of EOR method. (1) Cost effective production is the main challenge given the current economic situation of steady low oil prices. CO2 HnP has low injection cost and wide sources of the injection gas. (2) CO₂ HnP can be applied to reservoirs with different permeability, especially to shale reservoirs with poor response to water injection and severe water sensitivity. (3) The implementation of technology is simple. (4) The oil development effect and economic benefit are good and the risk is small. At the same time, there are some challenges when applying this technology. The EOR mechanisms are complex, leading to the difficulty of controlling the EOR effect. Another problem is that it's difficult to accurately predict the development effect as so many factors influencing the implement process. Thus, fully understanding the mechanisms of enhanced oil recovery and the influences of different injection parameters of this process are significant.

In this paper, we investigate the changes of formation oil phase behavior, saturation pressure, swelling factor, viscosity deduction when adding different percentage of CO_2 to understand the main interactions of injected CO_2 and formation crude oil. Then we conducted CO_2 HnP tests on shale core samples from Qianjiang depression in China. Matrix cores with different permeability and cores with natural fractures were all applied to evaluate the shale oil production potential. The influence of key factors (gas injection pressure, soaking time, permeability, miscible condition) on the performance of CO_2 huff and puff were discussed.

2. Interactions of CO₂ and formation crude oil

2.1. Physical properties of CO₂

 CO_2 exists in four forms: gas phase, liquid phase, solid phase and supercritical phase under different pressure and temperature conditions as shown in Fig. 1. The point at which the liquid and gas phase are in equilibrium is called the critical point. The critical temperature of CO_2 is about 31.2 °C, and the critical pressure is about 7.38 MPa. When the temperature and pressure are higher than the critical point, CO_2 is in supercritical condition. At this condition, the gasliquid interface disappeared, and its density is close to the density of a fluid. However, its viscosity and diffusion coefficient is still close to ordinary gas. The density of gas-phase CO_2 can be calculated by eqn (1). In different phase states, the density of CO_2 varies greatly, as shown in Fig. 2. The CO_2 density decreases as the system temperature increases or the system pressure decreases.

At a certain temperature, the liquid CO_2 density is not significantly affected by pressure. As the temperature rises, CO_2



Fig. 2 Density distribution curves under different pressures of CO₂.

changes from liquid phase to gas phase, leading to density decreases. When the system is in a supercritical state, the change of CO_2 density is greatly affected by system temperature and pressure.

$$\rho_{\rm CO_2} = \frac{pM_{\rm CO_2}}{ZRT} \tag{1}$$

View Article Online RSC Advances

2.2. The effect of CO₂ on formation oil phase behavior

The shale oil used in this paper is obtained from Qianjiang depression. The initial reservoir pressure is 18.62 MPa, and the



Fig. 1 CO₂ P–T phase behavior diagram (Copyright ©1999 ChemicaLogic Corporation).

 Table 1
 Shale oil composition of separator oil, separator gas, and formation crude oil

Oil composition	Separator oil	Separator gas	Formation crude oil
N_2	0	3.262	1.59
CO ₂	0	0.621	0.3
CH ₄	0.18	47.211	23.11
C_2H_6	0.22	13.139	6.52
C_3H_8	1.61	19.569	10.36
IC4	2.77	2.773	1.73
NC4	1.72	7.392	4.48
IC5	2.82	1.819	2.27
NC5	3.38	2.028	2.72
FC6	8.27	1.422	4.93
FC7	4.92	0.571	2.8
FC8	5.87	0.193	2.95
FC9	5.21	0	2.51
FC10	4.06	0	2.08
C11 to C41	58.97	0	31.65



Fig. 4 The changes of formation oil viscosity with different CO₂ mole fractions at reservoir condition (P = 18.62 MPa, T = 69.9 °C).

$$b = \frac{0.0778RT_{\rm c}}{p_{\rm c}} \tag{7}$$

temperature is 69.9 °C. The separator oil, separator gas, and formation crude oil compositions are presented in Table 1. The Peng–Robinson equation of state is used to calculate the phase behavior of CO_2 and crude oil system as shown in the following equations.

$$P = \frac{RT}{v-b} - \frac{\alpha(T)}{v(v+b) + bv - b^2}$$
(2)

$$\alpha(T) = \alpha(T)\alpha_{\rm c} \tag{3}$$

$$\alpha_{\rm c} = \frac{0.45724R^2T_{\rm c}^2}{p_{\rm c}}$$
(4)

$$\alpha(T) = [1 + k(1 - T_{\rm r}^{0.5})]^2$$
(5)

$$k = 0.37464 + 1.54226\omega - 0.26992\omega^2 \tag{6}$$

where v is the gas molar volume, m³ mol⁻¹; T_r is the relative temperature, T_c is the critical temperature, p_c is the critical pressure, MPa; ω is the eccentric factor.

In the process of CO_2 HnP, the injected CO_2 will affect the formation oil phase behavior. The EOS Peng–Robinson model was used to calculate the phase behavior of CO_2 and formation crude oil system under different CO_2 mole fraction, as shown in Fig. 3. It shows that with the increase of CO_2 content in the oil phase, the oil–gas two-phase zone enclosed by the bubble point line and the dew point line increases continuously. The critical temperature of the system gradually decreases, and the critical pressure of the system gradually increases. It also indicates that during CO_2 HnP, the bubble point pressure of crude oil increases after CO_2 is injected into the formation, which is beneficial to conduct solution gas drive and contribute to oil production.



Fig. 3 Phase behavior of crude oil and CO₂ system at different CO₂ mole fractions.

Paper



Fig. 5 The changes of formation oil swelling factor at different CO_2 mole fractions.

2.3. The effect of CO₂ on formation oil properties

During the gas HnP, when CO_2 is injected into the formation, some of the CO_2 will dissolve into the crude oil. The solubility of CO_2 is related to temperature, pressure, salinity, and molecular weight of crude oil. The CO_2 solubility decreases with the increase of salinity and the increase of crude oil molecular weight. The dissolved CO_2 will expand the volume of crude oil, changing the crude oil viscosity and density, and reducing



Fig. 6 The changes of formation oil saturation pressure at different CO_2 mole fractions.

interfacial tension. When CO_2 is dissolved in light oil, the volume is generally increased by 1.4–1.6 times; when CO_2 is dissolved in heavy oil, the volume is generally increased by 1.05–1.32 times. Fig. 4–6 shows the changes of oil viscosity, swelling factor, saturation pressure with different CO_2 mole fraction. It can be seen that with the CO_2 content increases from 0 to 65 mol%, the oil viscosity declines from 1.94 mPa s to 0.453 mPa s, the swelling factor increases to 1.492, and the saturation pressure increases from 10.86 MPa to 16.66 MPa. It illustrates that CO_2 will achieve obvious swelling and viscosity reduction effect when it is injected into a reservoir and fully contacted with formation crude oil.

3. CO₂ huff-n-puff experiments

3.1. Experimental materials

The core samples used in this study were cut from the outcrop of Qianjiang formation in China. A total of 3 cores were used in this study as presented in Fig. 7. We determine the porosity and permeability of the core samples using the pulse decay method by helium injection. The properties of the core samples are shown in Table 2. There are some micro-fractures in Core #2. Thus its total permeability is $2.67 \times 10^{-3} \ \mu m^2$, which is much higher than the permeability of the others. The oil used in the core saturation was the separated oil as shown in Table 1 with a density of $0.8545 \ g \ cm^{-3}$ and a viscosity of $3.49 \ cP$ at the temperature of 20 °C. Distilled water is used in the experiment to pressurize the syringe pump. The CO₂ used in this study was from Qingdao Tianyuan company, China, with a purity of 99.9%.

3.2. Experimental procedures

As shown in experiment schematic Fig. 8 and 9, the main instruments and equipment used in this experiment are CO_2 cylinder, core container, type II core container, pressure sensor, syringe pump, ISCO pump, accumulator, vacuum pump, and oven.

The HnP test contained two parts, including core sample saturation with crude oil and gas HnP process. During the core saturation oil process, the core samples were cleaned with toluene and dried in the oven at 70 °C for 36 h. Then the core samples were weighed and recorded as w_d . After that, the core samples were put into the type II core container and vacuumed for 48 h to completely remove the air in the pores. Crude oil was



(a) Core #1

(b) Core #2

(c) Core #3

Fig. 7 Qianjiang formation outcrop core samples used in this study

Table 2	Core	samples	specification	S
Table 2	Core	samples	specification	

Core no.	Length, m	Diameter, m	Porosity, %	Effective porosity, %	Matrix permeability, $(10^{-3} \mu m^2)$	Total permeability, $(10^{-3} \mu m^2)$
Core #1	4.85	2.49	14.5	12.75	0.034	0.034
Core #2	5	2.4	10.72	10.13	0.011	2.67
Core #3	5	3.7	8.6	7.78	0.008	0.008

then injected into the core container and a pressure of 30 MPa was maintained for one month to fully saturate the core samples. After these processes, the core samples were removed out and weighed as the saturated core w_s .

After saturation, the core sample was put into the HnP vessel. Before starting the experiment, we first test the whole system by injecting N₂ at a pressure of 20% higher than the designed experiment pressure and make sure no leakage during all the process. The flow chart of experimental equipment for HnP is shown in Fig. 9. The main procedures of CO₂ HnP include injection stage, soaking stage, and production stage. During the injection stage, the core sample was put into the type II container and CO₂ gas was injected into the container to the designed pressure (8 MPa/13 MPa/20 MPa). All valves were then closed during soaking period (0.5 h/3 h/8 h) to allow the injected CO₂ to fully contact and reacted with the oil in core sample. During the production process, the pressure of container was released to atmosphere pressure. The core sample was weighed again and record as w_i when the core mass is no longer changed (usually waiting for 6 hours). After these stages, the first HnP cycle is completed. Repeat the above steps to conduct more HnP cycles based upon experiment requirements.

The experimental operation schedule is shown in Table 3. The oil recovery factor of cycle i (R_i) can be calculated using eqn (8).

$$R_{\rm i} = \frac{w_{\rm s} - w_{\rm i}}{w_{\rm s} - w_{\rm d}} \times 100\% \tag{8}$$

3.3. Nuclear Magnetic Resonance (NMR) experiment

The NMR experiment in this study is to explore the sequence of oil recovered in different pore sizes during the HnP process. In this experiment, five different statuses, including the saturated core, the core after the first, second, fourth, and sixth cycles, were selected to do the NMR analysis. In the generated NMR spectrum, T2 relaxation time has a good correspondence with the shale pore radius. Longer T2 relaxation time results in a larger pore radius. Generally, pores with relaxation time distributed within the range of 0–1 ms are regarded as micropores. Pores with relaxation time within the range of 1–10 ms, 10–100 ms, and greater than 100 ms are small pores, mesopores, and macropores.⁴³ By comparing and analyzing the NMR T2 spectrum of residual oil distribution at the end of different CO_2 HnP cycle, the oil production and contribution of different pore sizes to the enhanced oil recovery can be obtained.⁴⁴

4. Results and discussion

4.1. The effect of different injection pressure on oil recovery

 CO_2 HnP tests were conducted on three core samples with the same soaking time of 0.5 h and different injection pressures, which were 8 MPa, 13 MPa, and 20 MPa. Each test has 6 HnP cycles. As shown in Fig. 10, CO_2 HnP is an effective method to enhance oil recovery in shale cores. After six HnP cycles, the oil recovery factor for Core #1 at injection pressures of 8, 13, and 20 MPa are 25.9%, 47.1%, and 55.4%, respectively. The results also indicate that all these three core samples with different permeability have a similar trend of performance. The oil recovery factor increased as the injection pressure increased. The oil recovered amount in one cycle during CO_2 HnP process is presented in Fig. 11. The oil recovery factor obtained in the first HnP cycle is the largest. In the subsequent HnP cycles, the recovered oil increment in each cycle gradually decreases and tends to be stable. For Core #2, the oil recovery differences for



Fig. 8 Schematic diagram of saturated oil experimental equipment.



three different injection pressures comes from the first three cycles, especially the first cycle. For Core #1 and Core #3, comparing the performance of injection pressures of 8 MPa and 13 MPa, the oil recovered in each cycle at low injection pressure is lower than that at higher injection pressure. However, for the oil recovery of injection pressures 13 MPa and 20 MPa, both exceeding the MMP of CO_2 and oil, the main difference of the oil recovery comes from the first three cycles. From the fourth cycle, there is not much difference in the amount of oil recovered in one cycle. This shows that under immiscible condition, the oil recovery increases as the injection pressure is not as significant as before. It also indicates that the injection pressure should be higher than MMP of the CO_2 and formation oil system to maintain a good EOR performance.

4.2. The effect of soaking time on oil recovery

It takes some time for CO_2 to dissolve into the crude oil after injected into the reservoir. Therefore, a period of shut-in time called soaking time is required after gas injection. Too short the soaking time will lead to insufficient contact between CO_2 and crude oil, which will affect the crude oil swelling. However, if the soaking time is too long, CO_2 may diffuse to the reservoir boundary, affecting the energy storage near the area of production well and causing a waste of time. In this section, Core #3 is used to explore the influence of different soaking time on shale oil recovery.

The variation of recovery factor with different soaking times of 0.5 h, 3 h, and 8 h under 3 different injection pressures are presented in Fig. 12. These three cases yield the similar trends that the longer the soaking time, the higher the oil recovery factor. The characteristics of low porosity and low permeability of shale cores determine that the substituted crude oil diffuses and flows slowly in the matrix. Comparing with the three

figures, we can find that when the injection pressure is low (8 MPa), the oil recovery factor increases as the soaking time increases. However, when the injection pressure becomes higher, the soaking time does not have a significant effect on oil production. It can be found that, when the injection pressure is 20 MPa, the oil produced in different cycles with a soaking time of 3 h is gradually close to that with a soaking time of 8 h. The advantages of long soaking time will gradually lose at high pressure. Therefore, there exists an optimal soaking time in the CO_2 HnP EOR method.

4.3. The effect of core permeability and fractures on oil recovery

In these three core samples, Core #2, with a permeability of 2.67 $\times 10^{-3} \ \mu\text{m}^2$, has fractures along the longitudinal section which can be observed from the cross-section of the core. There are no fractures on Core #1 and Core #3. The permeability of Core #1 is $0.034 \times 10^{-3} \ \mu\text{m}^2$, and the permeability of Core #3 is $0.008 \times 10^{-3} \ \mu\text{m}^2$. The performances of CO₂ HnP after six cycles at different injection pressures are shown in Fig. 13. The core with

Table 3	Experimental	operation	schedule
Tuble 5	Experimentat	operation	Jenedule

Cores	Injection pressure/MPa	Soaking time/h	Production time/h
Core #1	8	0.5	1
Core #2		3	
Core #3		8	
Core #1	13	0.5	
Core #2		3	
Core #3		8	
Core #1	20	0.5	
Core #2		3	
Core #3		8	

Fiq. 9

This article is licensed under a Creative Commons Attribution-NonCommercial 3.0 Unported Licence.

Open Access Article. Published on 13 September 2019. Downloaded on 8/9/2025 9:39:13 AM.

(cc) BY-NC

fractures has an oil recovery more than 17.8% higher than that of matrix cores at injection pressure of 8 MPa. With the injection pressure increases, the advantage of fractures become more obvious. When the injection pressures are 13 MPa and 20 MPa, the oil recovery factors are more than 20.4% and 24.3% than that without fractures. It illustrates that fractures play an



Fig. 10 Oil recovery factor curves of CO_2 HnP at different injection pressures.

Fig. 11 Oil recovered amount in one cycle during CO_2 HnP at different injection pressures.

Paper

important role in enhancing recovery efficiency during CO_2 HnP process. For the two cores without fractures, the difference of oil recovery is not significant (less than 3%) as the increase of the



Fig. 12 Soaking time effect on the CO_2 HnP performance with different pressure (Core #3).



Fig. 13 Matrix permeability and fracture effect on CO_2 huff-n-puff performance at different injection pressures (six HnP cycles, soaking time = 0.5 h).

matrix permeability. Fig. 14 presents the oil recovery factor at different HnP cycles at an injection pressure of 20 MPa for these three core samples. It indicates that the oil recovery factor difference comes from the first HnP cycle. In the subsequent cycle, fractures do not contribute much to the oil recovery. Thus, it indicates that the oil in fractures has small flow resistance due to the high fracture conductivity. During the CO_2 HnP process, the oil in the fractures with low resistance will be produced first. Then the oil in the pores will flow into the fracture and be displaced out in the following HnP cycles.

4.4. The effect of miscible condition on oil recovery

The measured minimum miscible pressure of CO_2 and crude oil was 12.75 MPa. The tests were conducted on Core #1 at a soaking time of 3 h Fig. 15 shows the final oil recovery factor of Core



Fig. 14 Matrix permeability and fracture effect on CO_2 huff-n-puff performance at different HnP cycle (P = 20 MPa, soaking time = 0.5 h).

#1 after 6 HnP cycles under different operating pressures. By observing the changes of oil recovery factor under different conditions including immiscible (8 MPa), near miscible (13 MPa) and miscible (20 MPa), we can obtain that the oil recovery factors change significantly when the operating conditions vary from immiscible to miscible. The oil recovery factor was 29.7% in the first HnP cycle when CO₂ injected at 13 MPa, and 63.7% of the oil was produced at the end of 6 HnP cycles. However, when the injection pressure was 8 MPa, the maximum oil recovery factor achieved for each cycle is much lower than that near miscible condition. Table 4 presents the oil recovered in each of the HnP cycle under three different conditions. It indicates that the increase rate of oil recovered gradually slowed down in the subsequent cycle compared with the previous one. In the last three cycles, the recovery rate gradually decreased. It can be seen that when the HnP cycle increases under miscible condition, the high pressure gradually loses its advantage. Thus, miscible condition is favorable for enhancing oil recovery than immiscible conditions. During the CO2 HnP process, there are three ways of material exchange exist: the injected CO₂ will selectively take up components from the oil phase (vaporizing mechanism), the oil may take up components from the gas phase (condensing mechanism), or both oil and gas may take up components from the other phase (combined vaporizing and condensing drive).45 In the immiscible condition, both gas phase and oil phase are present, the gas will have a higher mobility than the oil phase, and this may possibly lead to a gas breakthrough, which means the major part of the production will consist of gas. While, under miscible condition, only one phase is presented in the reservoir, which is advantageous for oil production.45

4.5. The microscopic oil production process with NMR tests

By comparing and analyzing the NMR T2 spectrum of microscopic residual oil distribution at the end of different CO_2 HnP



Fig. 15 Effect of different miscible conditions on oil recovery factor (Core #1).

 Table 4
 The increment of oil recovery factor on each injection cycles

 (Core #1)
 (Core #1)

HnP cycle number	Injection pressure			
	8 MPa	13 MPa	20 MPa	
Cycle 1	21.2	29.7	34.5	
Cycle 2	7.9	10.4	10.5	
Cycle 3	7.0	7.6	7.4	
Cycle 4	5.8	5.5	4.7	
Cycle 5	3.61	6	4.9	
Cycle 6	2.39	4.3	3.3	

cycles, the residual oil production with different pore sizes and its contribution to enhancing oil recovery can be obtained. Fig. 16 shows that there are two wave crests in the three core samples. The two wave crests in the spectrum of Core #1 indicate that the pores in Core #1 mainly consist of two sizes of pores. The crest on the left represents micropores and small pores, and the crest on the right represents relatively large pores. The higher the permeability, the larger the amplitude of right wave crest and the larger proportion of larger pore size. The spectrum of Core #2 has two crests, but there is little transition between the two crests. Moreover, the second wave crest is distributed around T2 relaxation time equals 100, indicating that right wave crest represents macropores which are fractures. The matrix of Core #2 was relatively homogeneous, with T2 relaxation time ranging from 0.1 to 2. Core #3 is also homogeneous with most of the oil is distributed on the left wave crest. While the amplitude of the right wave crest is small, indicating that the core is mainly composed of micro pores, with a few mesopores and macropores.

During the CO_2 HnP production, the distribution curve T2 spectrum gradually moves downward to the left, indicating that crude oil in the large pores comes out first, which is consistent with the study by Ma *et al.* (2019). The oil recovered in the first cycle was dominated by macropores and mesopores, followed by small pores. With the increase of the number of cycles, most of the removable oil in macropores and mesopores has been produced, the oil in small pores and micropores become the main oil-producing area.

4. Conclusions

In this study, the interaction of CO_2 and formation oil was discussed, and a series of experiments were conducted on the improvement of shale oil production by CO_2 HnP injection. Here, we summarize the main conclusions based on the experimental results.

(1) The purpose of CO_2 HnP is to keep the reservoir pressure high and influences the oil/gas phase equilibrium in the reservoir. The interactions of CO_2 and formation crude oil include oil viscosity decline, oil swelling, saturation pressure and critical pressure increasing, which are all beneficial to shale oil production.



Fig. 16 NMR T2 spectrum curve of remaining oil distribution after different cycle.

(2) The parameters affecting CO_2 HnP EOR performance include reservoir properties such as matrix permeability, induced fractures, and operation parameters such as injection pressure, soaking time, and miscible condition. The influences cannot be determined by one parameter, but needed to synthetically consider other factors together. In general, fracture is the fundamental factor affecting oil recovery as it connects oil and gas seepage channels and improves oil and gas percolate capacity. The injection pressure significantly affects the formation oil and gas displacement conditions including miscible or immiscible states. Soaking time is also influenced by injection pressure in the way that longer soaking time is needed when the injection pressure is low or under immiscible condition. However, the advantages of long soaking time will gradually lose at relatively high pressure. The oil recovery factor increases significantly when the operating conditions vary from immiscible to miscible condition. Upon the discussion in this paper, it is of great significant to determine the operating parameters to achieve a good CO_2 HnP EOR performance.

(3) The NMR tests show that the oil production process is dominated by the pore size distribution. The oil in the macropores and mesopores was produced firstly, followed by small pores and micropores. The oil in small pores and micropores become the main oil-producing area in the long term development of shale oil reservoirs.

Conflicts of interest

There are no conflicts to declare.

Acknowledgements

The work is supported by the Province Natural Science Foundation of Shandong (ZR2018BEE018), the National Natural Science Foundation of China (51904324, 51974348), China Postdoctoral Science Foundation (2018M630813, 2019T120616), the Fundamental Research Funds for the Central Universities (18CX02170A), the Postdoctoral Applied Research Project Foundation of Qingdao city (BY201802003), and the Funding for Scientific Research of China University of Petroleum East China (YJ20170013).

References

- 1 X. Tong, G. Zhang, Z. Wang, Z. Wen, Z. Tian, H. Wang, F. Ma and Y. Wu, Distribution and potential of global oil and gas resources, *Petrol. Explor. Dev.*, 2018, 45(04), 219–229.
- 2 M. M. Xue, G. Wu, Q. Wang, *et al.*, Socioeconomic impacts of a shortage in imported oil supply: case of China, *Natural Hazards*, 2018, 1–16.
- 3 C. Peter, N. J. Felipe, T. Lanardonne, *et al.*, Across the universe of shale resources—a comparative assessment of the emerging legal foundations for unconventional energy, *The Journal of World Energy Law & Business*, 2018, **11**(4), 283–321.
- 4 American Association of Petroleum Geologists, Energy Minerals Division, Unconventional Energy Resources: 2017 Review, *Nat. Resour. Res.*, 2019, **28**(4), 1661–1751.
- 5 B. Jia, J. S. Tsau and R. Barati, A review of the current progress of CO_2 injection EOR and carbon storage in shale oil reservoirs, *Fuel*, 2019, **236**, 404–427.
- 6 L. Li, J. J. Sheng, Y. Su, *et al.*, Further investigation of effects of injection pressure and imbibition water on CO_2 huff-n-

puff performance in liquid-rich shale reservoirs, *Energy Fuels*, 2018, **32**(5), 5789–5798.

- 7 L. Jin, S. Hawthorne, J. Sorensen, *et al.*, Advancing CO₂ enhanced oil recovery and storage in unconventional oil play–experimental studies on Bakken shales, *Appl. Energy*, 2017, **208**, 171–183.
- 8 T. Wan and Z. Mu, The use of numerical simulation to investigate the enhanced Eagle Ford shale gas condensate well recovery using cyclic CO₂ injection method with nanopore effect, *Fuel*, 2018, 233, 123–132.
- 9 R. Simon and D. J. Graue, Generalized correlations for predicting solubility, swelling and viscosity behavior of CO₂-crude oil systems, *J. Pet. Technol.*, 1965, **17**(1), 102–106.
- 10 J. J. Dooley, R. T. Dahowski and C. L. Davidson, The potential for increased atmospheric CO_2 emissions and accelerated consumption of deep geologic CO_2 storage resources resulting from the large-scale deployment of a ccs-enabled unconventional fossil fuels industry in the U.S, *Int. J. Greenhouse Gas Control*, 2009, 3(6), 720–730.
- 11 E. M. Winter and P. D. Bergman, Availability of depleted oil and gas reservoirs for disposal of carbon dioxide in the United States, *Energy Convers. Manage.*, 1993, 34(9–11), 1177–1187.
- 12 J. W. Choi, J. P. Nicot, S. A. Hosseini, *et al.*, CO₂ recycling accounting and EOR operation scheduling to assist in storage capacity assessment at a U.S. gulf coast depleted reservoir, *Int. J. Greenhouse Gas Control*, 2013, **18**, 474–484.
- 13 B. Iraji, S. R. Shadizadeh and M. Riazi, Experimental investigation of CO₂ huff and puff in a matrix-fracture system, *Fuel*, 2015, **158**, 105–112.
- 14 C. Song and D. Yang, Experimental and numerical evaluation of CO_2 huff-n-puff processes in Bakken formation, *Fuel*, 2017, **190**, 145–162.
- 15 S. Sharma, J. J. Sheng and Z. Shen, A comparative experimental study of huff-n-puff gas injection and surfactant treatment in shale gas-condensate cores, *Energy Fuels*, 2018, **32**(9), 9121–9131.
- 16 J. Ma, X. Wang, R. Gao, *et al.*, Enhanced light oil recovery from tight formations through CO_2 huff 'n'puff processes, *Fuel*, 2015, **154**, 35–44.
- 17 R. Sun, W. Yu, F. Xu, *et al.*, Compositional simulation of CO₂ huff-n-puff process in middle bBakken tight oil reservoirs with hydraulic fractures, *Fuel*, 2019, **236**, 1446–1457.
- 18 M. Tang, H. Zhao, H. Ma, *et al.*, Study on CO₂ huff-n-puff of horizontal wells in continental tight oil reservoirs, *Fuel*, 2017, **188**, 140–154.
- 19 X. Zhou, Q. Yuan, X. Peng, *et al.*, A critical review of the CO₂ huff 'n'puff process for enhanced heavy oil recovery, *Fuel*, 2018, 215, 813–824.
- 20 G. Lv, L. Qi, S. Wang and X. Li, Key techniques of reservoir engineering and injection-production process for CO₂ flooding in China's sinopec shengli oilfield, *J. CO₂ Util.*, 2015, **11**, 31–40.
- 21 H. Ziguo, Integrated techniques of underground CO₂ storage and flooding put into commercial application in the jilin oilfield, China, *Acta Geol. Sin.*, 2012, (1), 285.

- 22 C. Bardon, P. Corlay, D. Longeron, *et al.*, CO₂ huff-n-puff revives shallow light-oil-depleted reservoirs, *SPE Reservoir Eng.*, 1994, **9**(2), 92–100.
- 23 J. Thomas, T. V. Berzins, T. G. Monger, *et al.*, Light oil recovery from cyclic CO₂ injection: influence of gravity segregation and remaining oil, *SPE Annu. Tech. Conf. Exhib.*, 1990, SPE-20531-MS.
- 24 B. J. Miller, C. P. Bardon and P. Corlay, CO₂ huff 'n' puff field case: five-year program update, *SPE Permian Basin Oil Gas Recovery Conf.*, 1994, SPE-27677-MS.
- 25 F. Torabi and K. Asghari, Effect of operating pressure, matrix permeability and connate water saturation on performance of CO₂ huff-and-puff process in matrix-fracture experimental model, *Fuel*, 2010, **89**, 2985–2090.
- 26 L. Li, Y. Zhang and J. J. Sheng, Effect of the Injection Pressure on Enhancing Oil Recovery in Shale Cores during the CO_2 Huff-n-Puff Process When It Is above and below the Minimum Miscibility Pressure, *Energy Fuels*, 2017, **31**(4), 3856–3867.
- 27 K. Zhang, Experimental and numerical investigation of oil recovery from Bakken formation by miscible CO₂ injection, *SPE Annu. Tech. Conf. Exhib.*, 2016, SPE-184486-STU.
- 28 Y. Zhang, W. Yu, Z. Li, *et al.*, Simulation study of factors affecting CO₂ huff-n-puff process in tight oil reservoirs, *J. Pet. Sci. Eng.*, 2018, **163**, 264–269.
- 29 C. Song & D. Yang, Performance evaluation of CO₂ huff-npuff processes in tight oil formations, *SPE Unconventional Resources Conference Canada*, Calgary, Alberta, 5–7 Nov 2013.
- 30 T. D. Gamadi, J. J. Sheng, M. Y. Soliman; *et al.*, An experimental study of cyclic CO₂ injection to improve shale oil recovery, *SPE Improved Oil Recovery Symposium*, Tulsa, Oklahoma, USA, 12–16 April 2014.
- 31 L. Li and J. ,J. Sheng, Numerical analysis of cyclic CH_4 injection in liquid-rich shale reservoirs based on the experiments using different-diameter shale cores and crude oil, *J. Nat. Gas Sci. Eng.*, 2017, **39**, 1–14.
- 32 Y. Yu, L. Li and J. J. Sheng, Further discuss the roles of soaking time and pressure depletion rate in gas huff-n-puff process in fractured liquid-rich shale reservoirs, *SPE Annu. Tech. Conf. Exhib.*, 2016.

- 33 L. Li, Y. Su, Y. Hao, *et al.*, A comparative study of CO₂ and N₂ huff-n-puff EOR performance in shale oil production, *J. Pet. Sci. Eng.*, 2019, **181**, 106174.
- 34 H. H. Hsu and R. J. Brugman, CO₂ huff-puff simulation using a compositional reservoir simulator, SPE Annu. Tech. Conf. Exhib., 1986.
- 35 B. T. Hoffman, Comparison of various gases for enhanced recovery from shale oil reservoirs. *SPE Improved Oil Recovery Symposium*, Tulsa, Oklahoma, 14–18 April 2012.
- 36 W. Yu, H. R. Lashgari, K. Wu and K. Sepehrnoori, CO₂ injection for enhanced oil recovery in Bakken tight oil reservoirs, *Fuel*, 2015, **159**, 354–363.
- 37 Z. Meng, S. Yang, L. Wang, *et al.*, Investigation on numerical simulation of CO₂ huff and puff in tight oil reservoirs, *J. of Petrochem. Univ.*, 2016, **29**(6), 39–42.
- 38 J. Sun, A. Zou, E. Sotelo, *et al.*, Numerical simulation of CO₂ huff-n-puff in complex fracture networks of unconventional liquid reservoirs[J], *J. Nat. Gas Sci. Eng.*, 2016, **31**, 481–492.
- 39 P. Zuloagamolero, W. Yu, Y. Xu, *et al.*, Simulation Study of CO₂-EOR in tight oil reservoirs with complex fracture geometries, *Sci. Rep.*, 2016, **6**, 33445.
- 40 Z. Yuan, Y. Wei, Z. Li, *et al.* Simulation study of factors affecting CO₂ huff-n-puff process in tight oil reservoirs, *J. Pet. Sci. Eng.*, 2018, **163**, 264–269.
- 41 L. Sheng and L. Peng, Experimental and simulation determination of minimum miscibility pressure for a Bakken tight oil and different injection gases, *Petroleum*, 2017, **3**(1), 79–86.
- 42 J. J. Sheng, Critical review of field EOR projects in shale and tight reservoirs, *J. Pet. Sci. Eng.*, 2017, **159**, 654–665.
- 43 Zh. Li, Y. Sun, R. Hu, *et al.*, Quantitative analysis for nanopore structure characteristics of shales using NMR and NMR cryoporometry, *J. Eng. Geol.*, 2018, **26**(3), 758–766.
- 44 Q. Ma, Sh. Yang, D. Lv, *et al.*, Experimental investigation on the influence factors and oil production distribution in different pore sizes during CO₂ huff-n-puff in an ultrahigh-pressure tight oil reservoir, *J. Pet. Sci. Eng.*, 2019, **178**, 1155–1163.
- 45 K. S. Pedersen & P. L. Christensen, *Phase behavior of petroleum reservoir fluids*, CRC Press, 2007.