RSC Advances

PAPER

Cite this: RSC Adv., 2020, 10, 43592

Received 5th November 2020 Accepted 23rd November 2020

DOI: 10.1039/d0ra09421h

rsc.li/rsc-advances

1. Introduction

With rapid agricultural and industrial growth, water pollution has become a great challenge to human beings and any other forms of life. How to eliminate pollutants from water and restore ecological water has become our top priority. To address this issue, semiconductor photocatalysis has been regarded as an efficient approach for sewage water purification by utilizing solar energy.^{1,2} In recent years, many kinds of semiconductors, such as $TiO₂$ ³⁻⁵ BiOBr,⁶ Ag₃PO₄,⁷ SnO₂,⁸ etc, have been well explored in developing promising photocatalysts. Among them, titanium dioxide $(TiO₂)$ has attracted considerable attentions due to its outstanding photocatalytic activity, low cost, adorable chemical and thermal stability, corrosion resistance, nontoxicity and other favorable properties.⁹ However, as the n-type broad bandgap semiconductor, $TiO₂$ can only be excited by ultraviolet light to produce electron–hole pairs. Single phase $TiO₂$ also suffered from high rate recombination of photogenerated carriers. All these literally hindered its performance on practical applications.¹⁰

Crystalline phase regulation of anatase–rutile $TiO₂$ for the enhancement of photocatalytic activity for the enhancement of photocatalytic activity

Kuang Wang,^{ab} Yan Zhuo,^a Jiayi Chen,^a Dawei Gao,^a Yu Ren,^b Chunxia Wang^{ab} and Zhenm[i](http://orcid.org/0000-0001-9165-2589)ng Qi^{D*a}

Biphasic TiO₂ with adjustable crystalline phases was prepared by the hydrothermal-calcination method assisted by nitric acid (HNO₃) and hydrogen peroxide (H₂O₂), using potassium titanate oxalate $(K_2TiO(C_2O_4)_2)$ as the titanium source. The influences of H₂O₂ volume on anatase and rutile contents and photocatalytic activity of biphasic $TiO₂$ were investigated and the photocatalytic mechanism was explored. X-ray diffraction (XRD), scanning electron microscopy (SEM), transmission electron microscopy (TEM), X-ray photoelectron spectroscopy (XPS), UV-vis diffuse reflectance spectroscopy (UV-vis DRS) and specific surface area (BET) were employed to characterize crystal structure, physical morphology, absorbable light, chemical composition, specific surface area and pore size distribution. The photocatalytic degradation efficiency towards a methylene blue (MB) solution under xenon light was tested, and the photocatalytic stability of the sample was investigated by photocatalytic cycle experiments. The prepared biphasic $TiO₂$ was nanorod-shaped and had a large specific surface area. The results showed the anatase $TiO₂$ content increased and the photocatalytic efficiency was enhanced as the H_2O_2 volume solution increased. Among the catalysts, the biphasic TiO₂ prepared with 30 mL of H₂O₂ had the best photocatalytic effect and could entirely degrade the MB solution after 30 minutes under irradiation. After three repeated degradations, the photocatalytic degradation rate was still estimated to be as high as 95%. It is expected that the work will provide new insights into fabricating heterophase junctions of $TiO₂$ for environmental remediation. **PAPER**
 (a) Check for updates

Crystalline phase regulation of anatase-rutile Times and the control of the enhancement of photocatalytic activity
 $\frac{1}{2}$ Clientes *nsc* α , 2003, 20, 4392

Since the analytic phase

Semiconductors composite and heterophase interfaces are effective strategies to improve photocatalytic activity of $TiO₂$. Recently, more interests are mainly focused on the composite of semiconductors. For instance, TiO_2/WO_3 ,¹¹ $TiO_2/BiVO_4$,¹² $TiO_2/$ CuO,¹³ TiO₂/CdS,¹⁴ and *etc.*, are of great benefit for the transmission and detachment of photogenerated charge carriers.¹⁵ Zhu and his team presented a in situ synthesis technique in preparing g-C₃N₄/P25, and results revealed that g-C₃N₄/P25 has superior photodegradation performance than P25.¹⁶ BiOBr/TiO₂ nanorod heterojunction composite was prepared by Xue and his colleagues via electrochemical anodization method, and products exhibited remarkable reduction efficiency of $Cr(vl)^{17}$ According to Chi and his coworkers, porous $TiO₂$ nanotubes/ Ag_3PO_4 heterojunction was synthesized by facile electrospinning and chemical co-deposition route, and obtained sample featured an exceptive enhancement by the photodegradation of methylene blue.¹⁸ TiO₂ heterophase interfaces have been proved to have more superior photocatalytic activity than pure anatase or rutile phase TiO₂ by many researchers. Lyu et al.¹⁹ fabricated a TiO₂ hollow heterophase junction by coating anatase $TiO₂$ hollow spheres with porous amorphous $TiO₂$, and the obtained $TiO₂$ exhibited preferable adsorption capability, light harvesting ability, and charge-separation efficiency. It was reported that $TiO₂$ heterophase junction had controllable contact area between

^aCollege of Textiles and Clothing, Yancheng Institute of Technology, Yancheng, China. E-mail: cxwang@mail.dhu.edu.cn

b School of Textile and Clothing, Nangtong University, Nantong, China

rutile and anatase phase, which is favorable for the separation and transition of photo-generated carriers at the heterojunction region.²⁰ E et al.²¹ reported that various contents of hydrochloric acid could lead to different crystallizations of TiO₂. Biphasic TiO₂ with different contents of anatase and rutile have been successfully prepared in an acidic hydrothermal system by Li et $al.^{22}$ Tartaric acid $(C_4H_6O_6)$ was employed as the phase content regulator and $TiCl₃$ as the titanium source, and result demonstrated that $TiO₂$ with 77% anatase and 23% rutile had the optimized photocatalytic performance. However, $K_2TiO(C_2O_4)_2$ as precursor and H_2O_2 as phase content regulator to adjust the anatase and rutile contents of biphasic $TiO₂$ has not been reported. Hence, it is of profound significance to adjust the anatase and rutile contents to further study the photocatalytic performance of biphasic TiO₂. Paper

Track and antase phase, which is forest
be for the separation redshifted for the separation and the straighted on FINA: Diff atomicinal and common

and consider article is licensed common and the straighted on 11/2

This work aims to promote the photodegradation of organic pollutants by synthesizing a novel kind of spindle-like biphasic $TiO₂$ nanorods *via* hydrothermal-calcination route. The anatase and rutile contents in biphasic $TiO₂$ were adjusted by controlling different volumes of H_2O_2 . The influence of H_2O_2 volume on the photocatalytic performance of biphasic $TiO₂$ was discussed and the mechanism of photocatalytic degradation was explored.

2. Experimental

2.1. Materials

Potassium titanium oxalate $(K_2TiO(C_2O_4)_2)$ was purchased from Shanghai Titan Technology Co., Ltd. (Shanghai, China). Hydrogen peroxide $(H₂O₂, 30%)$ and nitric acid $(HNO₃, 65%)$ were provided by Jiangsu Tongsheng Chemical Reagent Co., Ltd. (Wuxi, China). Absolute ethanol was obtained from Sinopharm Chemical Reagent Co., Ltd. (Shanghai, China). All the reagents were of analytical grade and used without further purification.

2.2. Sample preparation

In a typical synthetic procedure: $K_2TiO(C_2O_4)_2$ (5 mmol) was completely dissolved in a certain volume of H_2O_2 (30%) and deionized water under magnetic stirring to obtain a mixture solution of 50 mL. 65% $HNO₃$ (1.7 mL) was added dropwise into the aforementioned solution to obtain the precursor solution. The solution was then sealed within a Telfon-lined autoclave (150 mL) and maintained 150 °C for 12 h. After the vessel was cooled down to room temperature naturally, the precipitate was centrifuged and washed three times by deionized water and absolute ethanol, and dried at 60 °C. Subsequently the dry powder was calcined at 500 °C in muffle furnace for 4 h and pulverized to biphasic $TiO₂$ powder. The volumes of 30% H_2O_2 were 0 mL, 5 mL, 10 mL, 15 mL, 20 mL, 25 mL and 30 mL, and the samples were denoted as S-0, S-5, S-10, S-15, S-20, S-25 and S-30, respectively.

2.3. Characterization

The X-ray diffractometer (XRD) (PANalytical, Dutch) was performed to analyze the phase of the obtained sample. The morphology of the sample was observed by Nova Nano SEM 450

field emission scanning electron microscope (FEI, America) and JEM-2100F field emission transmission electron microscope (JEOL, Japan). Optical absorption spectrum was detected by TU-1901 UV-vis DRS (Persee, China). The elemental composition was further revealed by ESCALAB 250Xi X-ray photoelectron spectrometer model (Thermo Fisher Scientific, America). A fully automatic specific surface and pore analyzer model TriStar II 3020 (Micromeritics, America) was applied to evaluate the specific surface area, total pore volume, and average pore diameter of the sample.

2.4. Photocatalytic activity measurement

Methylene blue (MB) was employed as a simulated pollutant. A time-dependent experiment was conducted to investigate the photocatalytic activity in the degradation of MB by the asprepared sample. Typically, the sample (0.1 g) was scattered into MB solution (100 mL, 20 mg L^{-1}). Before light illumination, the mixed suspension of MB and sample were stirred for 30 min to reach the adsorption–desorption equilibrium. Therewith the mixed solution was irradiated by a 300 W Xe lamp (LS-SXE300/ 300UV). MB solution (3 mL) was sampled at 5 min interval and centrifuged to remove the particles. The absorbance of MB solution was recorded by the maximum absorption-band at $\lambda =$ 664 nm on a UV-vis spectrophotometer.

Repeat experiments were carried out to evaluate the photocatalytic stability of the sample. S-30 was selected as the target object. After the first photocatalytic degradation, aqueous MB (2 mL, 1 $g L^{-1}$) and deionized water were consecutively added in the residual solution to obtain mixed solution (100 mL). The above process was repeated two times to test the duration of the photocatalytic performance. The photocatalytic activity of the sample was determined by degradation rate, which was calculated by eqn (1):

$$
\eta = \frac{C_0 - C_t}{C_0} \times 100\% = \frac{A_0 - A_t}{A_0} \times 100\% \tag{1}
$$

where C_0 and C_t are the concentration of MB before and after irradiation, respectively. A_0 and A_t are the absorbance of MB solution at the maximum absorption peak ($\lambda_{\text{max}} = 664 \text{ nm}$) before and after irradiation, respectively.^{23,24}

Langmuir-Hinshelwood pseudo-first-order kinetic model was applied to investigate the kinetics of photocatalytic performance in the photodegradation of MB, as demonstrated in eqn (2):

$$
\ln(C_0/C_t) = Kt \tag{2}
$$

where C_0 and C_t are the concentration of MB before and after irradiation, respectively. K is the pseudo first-order rate constant and t is the irradiation time. The linear slope of $ln(C_0/$ C_t)corresponding to t is applied to represent the value of K ²⁵

3. Results and discussion

3.1. XRD analysis

Fig. 1 illustrates the XRD patterns of biphasic TiO₂ prepared with different H_2O_2 volumes. As shown in Fig. 1, XRD diffractogram of TiO₂ exhibited the main peaks at 25.28° , 36.98°, 37.93°, 48.34°, 53.99°, 54.93°, 62.69°, 68.84°, 70.09° and 75.03, corresponding to (101), (103), (004), (200), (105), (211), (204), (113), (220) and (215), which coincided with the tetragonal anatase TiO₂ (JCPDS no. 21-1272). The main XRD peaks of rutile TiO₂ at about 27.33°, 36.09°, 41.23°, 44.14°, 54.36°, 56.46 $^{\circ}$ could be indexed to (110), (101), (111), (210), (211) and (220), which were in accordance with the standard card (JCPDS no. 21-1276). No other diffraction peaks were observed in the XRD pattern, indicating no other impurities generated in the preparation of $TiO₂$. All the patterns suggested the existence of anatase and rutile crystalline phases. The content of rutile phase was calculated by eqn (3):

$$
W_{\rm R} = \frac{I_{\rm R}}{0.886I_{\rm A} + I_{\rm R}}\tag{3}
$$

where W_R is the mass fraction of rutile crystalline phase, I_A and I_R are the diffraction peak intensity of anatase phase $2\theta =$ 25.2° and rutile phase $2\theta = 27.4^{\circ}$.²⁶

Fig. 2 depicts the influence of H_2O_2 volume on the contents of anatase and rutile in the biphasic TiO₂. With increasing H_2O_2 volume, the contents of anatase $TiO₂$ and rutile $TiO₂$ enhanced and declined, respectively. The as-prepared sample contained more rutile TiO₂ than anatase TiO₂ without the presence of $H₂O₂$, which could be ascribed to the remarkable differences in the growing rate and surface energy. When H_2O_2 was added, anatase TiO₂ gradually came up with rutile TiO₂ in content and outnumbered rutile ultimately. The explanation might be that: hydrolysis occurred in $K_2TiO(C_2O_4)_2$ to generate hydrogen titanate, which was likely transformed into rutile $TiO₂$ under the acid condition.²⁷ With the addition of H_2O_2 , $[C_2O_4]^{2-}$ was substituted by excess O^{2-} in the acid medium from H_2O_2 to form peroxo-complexes.²⁸ Afterwards, the oxygen was released *via* a complex decomposition reaction, and amorphous $TiO₂$ accumulated toward oxygen and anatase $TiO₂$ was formed as a result. The TiO₆ octahedron was inclined to face sharing, leading to more generation of anatase $TiO₂$. More oxygen was produced as the increasing addition of H_2O_2 , which further enhanced the anatase content. The entire reactions can be formulated as follows: RSC Advances

Signal of Tib, collined the main peaks at 32.3%
 (204) , (193), (203) and (213), shelic coloridate with the terms

collinear CO₂) (CO2), (193), (203) and (213), shelic considered with the terms

and the m

Fig. 1 XRD patterns of TiO₂ prepared with different volumes of H_2O_2 : (a) S-0, (b) S-5, (c) S-10, (d) S-15, (e) S-20, (f) S-25 and (g) S-30.

Fig. 2 Influence of H_2O_2 volume on the contents of anatase and rutile in biphasic $TiO₂$.

Hþ

$$
K_2 TiO(C_2 O_4)_2 + 2H_2 O_2 + H_2 O \rightarrow TiO_2 + K_2 CO_3 + 3H_2 CO_3
$$
(4)

$$
H_2O_2 \xrightarrow{H_2} O_2 + H_2O \tag{5}
$$

3.2. SEM observation

The morphology of as-synthesized samples was observed by SEM. As illustrated in Fig. 3, the morphologies of biphasic $TiO₂$ before and after calcination were spindle-like nanorods, which were approximately 300 nm in length and 50 nm in width. It was considered that the biphasic $TiO₂$ before calcination was prone to agglomerate. And the biphasic $TiO₂$ after calcination possessed more distinctive nanorod shape.

3.3. TEM observation

Fig. 4 reveals the TEM images of S-30. From Fig. 4(a), the aggregates were assembly of spindle-like nanorods with length of about 300 nm and width of about 50 nm, which was in agreement with the SEM observation. Fig. 4(b) indicated that the mesoporous structure was distributed in the biphasic $TiO₂$ nanorod, suggesting that the prepared biphasic $TiO₂$ was a mesocrystalline material. HRTEM image of biphasic $TiO₂$ is displayed in Fig. 4(c). The lattice fringe spacings of $d =$ \sim 0.32 nm and 0.23 nm were consistent with (110) crystal plane of rutile TiO₂ and (004) crystal plane of anatase TiO₂, separately. The result of HRTEM was well in accordance with XRD pattern, which further confirmed that the as-prepared $TiO₂$ had a biphasic structure.

3.4. UV-vis DRS analysis

The UV-vis DRS of S-30 and P25 are illustrated in Fig. 5. It was worth noting that the prepared biphasic $TiO₂$ and P25 basically had no absorption property in the visible light region (>420 nm) but outstanding absorption in the ultraviolet light region. The absorption edges estimated for S-30 and P25 were at 404 nm and 394 nm, which were corresponding to band gaps of 3.07 eV

Fig. 3 SEM photos of S-30: (a) before calcination ($\times 100$ 000), (b) before calcination ($\times 200$ 000), (c) after calcination ($\times 100$ 000) and (d) after calcination $(x200000)$.

and 3.15 eV, respectively. It was noted that S-30 performanced better photocatalytic activity compared to P25. One of the possible reason was that narrow band gaps of nanophotocatalyst lead to high utilization of visible light.

3.5. XPS analysis

Fig. 6 demonstrates the XPS spectrum of biphasic $TiO₂$ and the peak fitting diagrams of each constituent element. As shown in Fig. 6(a), the peak at 284.8 eV belonged to the characteristic peak of C 1s, which could be ignored as that may be the oilcontaminated carbon brought by the measuring instrument. It was observed that the biphasic $TiO₂$ was composed of two elements, titanium and oxygen. Fig. 6(b) displayed the Ti 2p spectrum, the peaks at 464.5 eV and 458.7 eV in the illustration were consistent with Ti $2p_{1/2}$ and Ti $2p_{3/2}$ respectively. The interval between the two peaks was 5.7 eV, which featured

Fig. 4 TEM and HRTRM images of S-30: (a), (b) TEM and (c) HRTEM.

typical characteristics of Ti^{4+} .²⁹ Fig. 6(c) exhibited two fitted peaks of the O 1s spectrum at 530.4 eV and 532.2 eV, which were the binding energies indexed to lattice oxygen and the hydroxyl group $(-OH).$ ³⁰

3.6. BET analysis

In order to further prove that the prepared $TiO₂$ was a mesoporous material, specific surface area, pore volume and average diameter of S-30 were measured by adsorption–desorption isotherm and pore size distribution curve illustrated in Fig. 7. The isotherm exhibited type IV with a H3 type hysteresis loop, indicating the mesoporous structure of $S-30$.^{28,31} S-30 possessed high specific surface area of \sim 54.16 m² g⁻¹ with total pore volume of ~ 0.2893 cm³ g⁻¹ and average pore diameter of \sim 21.36 nm, which were consistent with the TEM observation and the prepared sample was proved to be mesogenic. A large specific surface area and small pore size provide many favorable advantages including supplying more active sites, improving light absorption and utilization, and increasing the contact area with degraded contaminants. They are also conducive for the nano-photocatalysis to the transport of photogenerated carriers. Thereby S-30 exhibited an exceptional high photocatalytic activity.

3.7. Photocatalytic performance and stability

Fig. 8(a) presents photocatalytic degradation curves of TiO₂ prepared with different H_2O_2 volume. As can be observed, all the prepared biphasic $TiO₂$ had excellent photodegradation towards MB solution within 30 min, in that biphasic $TiO₂$ can

Fig. 6 XPS spectra of S-30: (a) survey, (b) Ti 2p peak fitting and (c) O 1s peak fitting.

Fig. 7 $\,$ N₂ adsorption–desorption isotherm and the pore size distribution curve of S-30.

form heterogeneous interfaces, separate electron–hole pairs and inhibit the recombination of carriers. The photocatalytic activity of the samples ascended with the increase in anatase content, because anatase has preferable photocatalytic performance than rutile.^{32,33} Thereinto, S-30 with the anatase content of 90.33% had the highest photodegradation rate on MB solution. The pseudo-first-order kinetic curves of the photocatalytic degradation of MB solution by biphasic $TiO₂$ are shown in Fig. 8(b), the pseudo-first-order rate constant K enlarged with increasing anatase content. S-30 exhibited superior photocatalytic activity $(K = 0.19159 \text{ min}^{-1})$ than P25 $(K =$ 0.13251 min⁻¹) in the decomposition of MB solution.

The repeated experiments of MB photodegradation were conducted to evaluate S-30 stability. After three consecutive reaction cycles, it was observed that S-30 exhibited no obvious decrease in the photocatalytic activity, the photodegradation rate was reduced by 5% in Fig. 9. The results demonstrated that S-30 had appreciable stability to photocatalyze the degradation of organic contaminants.

3.8. Photocatalytic mechanism

According to all above results, the schematic of photocatalytic mechanism of biphasic $TiO₂$ is illustrated in Fig. 10. The bandgaps of anatase $TiO₂$ and rutile $TiO₂$ were 3.2 eV and 3.03 eV.³⁴ The electrons of the biphasic TiO₂ were stimulated and transferred to the conduction band (CB) under light illumination. Owing to the difference in the band potentials, the photogenerated electrons transferred from the rutile CB to the anatase CB. Simultaneously the photogenerated holes migrated from the valence band (VB) of anatase to the rutile VB, resulting in the formation of anatase and rutile heterogeneous interfaces.³⁵ The biphasic $TiO₂$ composed of anatase and rutile therefore had an excellent charge separation efficiency, which improved the photocatalytic activity of the biphasic $TiO₂$.

Fig. 9 Cycling runs of S-30.

Fig. 8 Photocatalytic degradation of MB solution by biphasic TiO₂ and P25: (a) photodegradation curves and (b) pseudo-first-order kinetic curves.

Fig. 10 Schematic of photocatalytic mechanism of biphasic TiO₂.

4. Conclusions

The biphasic $TiO₂$ was successfully synthesized in the presence of $HNO₃$ and $H₂O₂$ via hydrothermal-calcination route, with $K_2TiO(C_2O_4)$ ₂ as titanium source. By changing the H_2O_2 volume, the ratio of anatase and rutile in the biphasic $TiO₂$ was adjusted. The content of anatase $TiO₂$ and its photocatalytic activity improved with the addition of H_2O_2 . When the H_2O_2 volume reached 30 mL, the biphasic $TiO₂$ composed of 90.33% anatase and 9.67% rutile was spindle-like nanorods and exhibited excellent photocatalytic efficiency and stability. After three times of repeated experiments, the photocatalytic degradation rate of MB solution remained as high as 95%. The adjustment of the anatase and rutile contents provides a neoteric strategy for other semiconductor heterogeneous junction materials to enhance the photocatalytic activity. PSC Advances

From $\frac{1}{2}$ The means of the state of $\frac{1}{2}$ Equal on $\frac{1}{2}$ Equa

Conflicts of interest

There are no conflicts to declare.

References

- 1 M. Ye, Z. Chen, W. Wang, J. Shen and J. Ma, J. Hazard. Mater., 2010, 184, 612–619.
- 2 I. J. Ani, U. G. Akpan, M. A. Olutoye and B. H. Hameed, J. Cleaner Prod., 2018, 205, 930–954.
- 3 I. Ali, M. Suhail, Z. A. Alothmanc and A. Alwarthan, RSC Adv., 2018, 8, 30125–30147.
- 4 Y. Lan, Y. Lu and Z. Ren, Nano Energy, 2013, 2, 1031–1045.
- 5 A. Miyoshi, S. Nishioka and K. Maeda, Chem.–Eur. J., 2018, 24, 18204–18219.
- 6 B. Zhang, M. Zhang, L. Zhang, P. A. Bingham, W. Li and S. Kubuki, Appl. Surf. Sci., 2020, 530, 147233.
- 7 Y. Zhang, G. Duoerkun, Z. Shi, W. Cao, T. Liu, J. Liu, L. Zhang, M. Li and Z. Chen, J. Colloid Interface Sci., 2020, 571, 213–221.
- 8 D. Zhao and X. Wu, Mater. Lett., 2018, 210, 354–357.
- 9 J. Hu, S. Zhang, Y. Cao, H. Wang, H. Yu and F. Peng, ACS Sustainable Chem. Eng., 2018, 6, 10823–10832.
- 10 E. Assayehegn, A. Solaiappan, Y. Chebude and E. Alemayehu, Appl. Surf. Sci., 2020, 515, 145966.
- 11 G. Žerjav, M. S. Arshad, P. Djinović and J. Zavašnik, Appl. Catal., B, 2017, 209, 273–284.
- 12 Y. Wang, N. Lu, M. Luo, L. Fan, K. Zhao, J. Qu, J. Guan and X. Yuan, Appl. Surf. Sci., 2019, 463, 234–243.
- 13 K. K. Mandari, B. S. Kwak, A. K. R. Police and M. Kang, Mater. Res. Bull., 2017, 95, 515–524.
- 14 L. Luo, J. Long, S. Zhao, J. Dai, L. Ma, H. Wang, L. Xia, L. Shu and F. Jiang, Process Saf. Environ. Prot., 2019, 130, 77–85.
- 15 H. Tong, S. Ouyang, Y. Bi, N. Umezawa, M. Oshikiri and J. Ye, Adv. Mater., 2012, 24, 229–251.
- 16 H. Zhu, D. Chen, D. Yue, Z. Wang and H. Ding, J. Nanopart. Res., 2014, 16, 2632.
- 17 C. Xue, T. Zhang, S. Ding, J. Wei and G. Yang, ACS Appl. Mater. Interfaces, 2017, 9, 16091–16102.
- 18 C. Chi, J. Pan, M. You, Z. Dong, W. Zhao, C. Song, Y. Zheng and C. Li, J. Phys. Chem. Solids, 2018, 114, 173–178.
- 19 J. Lyu, L. Zhou, J. Shao, Z. Zhou, J. Gao, Y. Dong, Z. Wang and J. Li, Chem. Eng. J., 2020, 391, 123602.
- 20 X. Zuo, K. Chang, J. Zhao, Z. Xie, H. Tang, B. Li and Z. Chang, J. Mater. Chem. A, 2016, 4, 51–58.
- 21 L. E, C. Hu, K. Hu, W. Zhao, J. Cui, Q. Xiong, Z. Guo and Z. Liu, Solid State Sci., 2019, 88, 36–40.
- 22 H. Li, X. J. Shen, Y. D. Liu, L. Z. Wang, J. Y. Lei and J. L. Zhang, J. Alloys Compd., 2015, 646, 380–386.
- 23 C. X. Wang, Y. Ren, J. C. Lv, Q. Q. Zhou, Z. P. Ma, Z. M. Qi, J. Y. Chen, G. L. Liu, D. W. Gao, Z. Q. Lu, W. Zhang and L. M. Jin, Appl. Surf. Sci., 2017, 396, 1840–1848.
- 24 K. K. Hu, L. E, D. Zhao, C. Y. Hu and J. Cui, CrystEngComm, 2018, 20, 3363–3369.
- 25 Z. M. Qi, K. Wang, Y. L. Jiang, Y. P. Zhu, X. M. Chen, Q. Tang, Y. Ren, C. H. Zheng, D. W. Gao and C. X. Wang, Cellulose, 2019, 26, 8919–8937.
- 26 W. W. Fu, G. D. Li, Y. Wang, S. J. Zeng, Z. J. Yan, J. W. Wang, S. G. Xin, L. Zhang, S. W. Wu and Z. T. Zhang, Chem. Commun., 2018, 54, 58–61.
- 27 J.-K. Oh, J.-K. Lee, H.-S. Kim, S.-B. Han and K.-W. Park, Chem. Mater., 2010, 22, 1114–1118.
- 28 L. L. Lai, L. L. Huang and J. M. Wu, RSC Adv., 2014, 4, 49280-49286.
- 29 J. M. Wu and H. X. Xue, J. Am. Ceram. Soc., 2009, 92, 2139– 2143.
- 30 Y. Luo, J. Luo, W. Zhou, X. Qi, H. Zhang, D. Y. W. Yu, C. M. Li, H. J. Fan and T. Yu, J. Mater. Chem. A, 2013, 1, 273–281.
- 31 M. Thommes, K. Kaneko, A. V. Neimark, J. P. Olivier, F. Rodriguez-Reinoso, J. Rouquerol and K. S. W. Sing, Pure Appl. Chem., 2015, 87, 1051–1069.
- 32 S. Lee, A. Y. Cho, Y. S. Rim, J. Y. Park and T. Choi, Coatings, 2020, 10, 557.
- 33 J. F. Zhang, P. Zhou, J. J. Liu and J. G. Yu, Phys. Chem. Chem. Phys., 2014, 16, 20382–20386.
- 34 V. Pfeifer, P. Erhart, S. Li, K. Rachut, J. Morasch, J. Brötz, P. Reckers, T. Mayer, S. Rühle, A. Zaban, I. Mora Seró, J. Bisquert, W. Jaegermann and A. Klein, J. Phys. Chem. Lett., 2013, 4, 4182–4187.
- 35 L. Li, M. Zhang, Y. Liu and X. Zhang, J. Colloid Interface Sci., 2014, 435, 26–33.