RSC Applied Interfaces

PAPER

Cite this: DOI: 10.1039/d4lf00266k

Reaction intermediates recognized by in situ FTIR spectroscopy in $CO₂$ hydrogenation over the Cu/ ZnO/SPP-zeolite catalyst†

Xiaolong Liu,^{abc} Guangy[in](http://orcid.org/0000-0001-9373-8685)g Fu,*bc Qiaolin Lang,^{bc} Ruiqin Ding,^{bc} Qiangsheng Guo,^d Ke Liang, ^e Shuman Gao, ^{bc} Xiaobo Yang ^{D bc} and Bing Yu^{*a}

Cu/ZnO nanoparticles embedded in zeolites possess smaller particle sizes than those in the conventional Cu/ZnO/Al₂O₃ catalyst. Therefore, they exhibit a distinctive manner of interaction with the reactants in the catalytic hydrogenation of $CO₂$ to methanol. The present paper uses in situ FTIR spectroscopy to recognize the introduction and removal of various carbonates, carbonyl, formates and water species adsorbed on the surface of a Cu/ZnO/SPP-zeolite catalyst in reactive flows. Together with other characterization results, such as quasi-in situ XPS, it was revealed that the Cu surfaces have an uneven electronic distribution and that constant carbonate coverage, low water adsorption, and fast consumption of carbonyls and formates are associated with the high conversion frequency of $CO₂$ over the Cu/ZnO/zeolite material. **PAPER**
 PAPER
 PAPER
 PAPER
 Reaction intermediates recognized by *in situ* **FTI

Creating observations assumption of CO**₂ hydrogenation over the Cu
 Specific Schemes and the Specific Schemes ($\frac{20}{3}$ **(\frac{2**

Received 24th July 2024, Accepted 14th September 2024

DOI: 10.1039/d4lf00266k

rsc.li/RSCApplInter

Introduction

The catalytic hydrogenation of $CO₂$ to methanol and other chemicals is under intensive study with respect to the utilization of captured $CO₂$ (CCUS) and the storage of volatile renewable energies in liquids. $¹$ An industrial project has been</sup> in operation in Iceland since 2002 at 2000 MT per an to convert $CO₂$ to methanol using a catalyst with Cu/ZnO/Al₂O₃ composition and has successfully demonstrated the importance of the process in reducing the carbon footprint per unit of energy production.² However, the technology is not yet competitive against the conventional syngas-tomethanol process due to several reasons. Firstly, the $CO₂$ conversion and CH3OH yields are thermodynamically restricted when $CO₂$ becomes the main carbon feed instead of CO. Secondly, equimolar H_2O is produced per CO_2 conversion, which accelerates metal sintering and shortens the catalyst's lifetime. Therefore, new catalysts with high activity and high sintering resistance are still desired to

 b Key Laboratory of Photoelectric Conversion and Utilization of Solar Energy, Qingdao Institute of Bioenergy and Bioprocess Technology, Chinese Academy of Sciences, 266101 Qingdao, China. E-mail: fugy@qibebt.ac.cn

^c Shandong Energy Institute, 266101 Qingdao, China

achieve higher space–time yields of methanol and to extend the catalyst lifetime.^{3,4} Modifications of Cu-based catalysts, including the addition of promoters, changes in the preparation processes and the replacement of Al_2O_3 supports as well as explorations of catalysts of new compositions, are being investigated.⁵⁻⁷ This work presents a study of a composite material with Cu/ZnO nanoparticles entrapped in the mesopores of the self-pillared pentasil (SPP) zeolite, which shows an improved catalytic activity.

Reducing the particle size is generally an effective way of improving the activity of metal catalysts.^{8,9} Moreover, zeolites are a type of microporous crystalline material with typical pore diameters of 0.4–1.0 nm, which are used as supports to confine and stabilize ultra-small metal particles. $8,10$ Metal species are loaded into the micropores of zeolites through diverse preparative routes, such as ion-exchange, chemical deposition, and impregnation.¹¹⁻¹³ Metal particles larger than 1 nm can be embedded in zeolite crystals with hierarchical micropore and mesopore systems.¹⁴ For example, Hu et al. used a Cu/Zn binary metal–organic framework material as a precursor and grew Na-ZSM-5 zeolite around it.15 After calcination in air, the MOF precursor was converted to about 2 nm Cu/ZnO particles enclosed in the zeolite crystals. The material exhibited a significantly higher methanol space– time-yield than that of the Cu/ZnO/Al₂O₃ catalyst. Ding et al. prepared 2–5 nm Cu particles in Na-beta zeolite through another procedure.16 The mesopores of a Na-beta zeolite with a hierarchical porous system were impregnated with a Cu salt precursor. Then, a microporous protective shell was grown on the crystal surfaces. After calcination and reduction, the metal nanoparticles remain immobilized in the crystals. In the

^a College of Chemistry and Chemical Engineering, Qingdao University, 266071 Qingdao, China. E-mail: yubing198@qdu.edu.cn

^d School of Chemical and Environmental Engineering, Shanghai Institute of Technology, 201418 Shanghai, China

^e Tianjin Passion Advanced Material Technology LLC, TEDA, 300280 Tianjin, China † Electronic supplementary information (ESI) available: The synthesis and basic characterization of the starting SPP zeolite, and additional quasi-in situ XPS and in situ FTIR spectra. See DOI: <https://doi.org/10.1039/d4lf00266k>

catalytic test, the desorption of C1 intermediates out of the zeolite was hindered, and the subsequent reactions forming ethanol were promoted, obtaining significant yields.

In a recent study, ultra-fine Cu particles of 1–2 nm size were entrapped in the grain boundaries of a silicalite-1 zeolite,¹⁷ which has a morphology of *ca*. 100 nm spheres made of \sim 20 nm grains.^{17,18} In situ FTIR spectroscopy was useful to monitor the generations and transformations of the reaction intermediates.

Adsorbed carbonyls, carbonates, formates and formic species were observed, implying that $CO₂$ was converted on the ultra-fine Cu particles through both the formate pathway and reversed water-gas-shift pathway, similar to that of the conventional Cu/ZnO/Al₂O₃ catalyst,^{19,20} which typically have Cu particles sizes in the range of $10-20$ nm.²¹ However, the formate intermediates were converted faster than carbonyl intermediates over the smaller Cu particles, indicating that the formate pathway was preferential for this catalyst and improved the methanol selectivity.

Through the addition of ZnO, the zeolite-supported smaller Cu particles can be further optimized. The role of ZnO in the $Cu/ZnO/Al₂O₃$ catalyst has been extensively investigated. It is known that ZnO serves as an electronic modifier, $20,22-24$ i.e., the oxide plays multiple roles to fine-tune the surface charges of Cu particles, acting as a bulky support and overlayers and with a small amount of Zn atoms alloyed into the Cu particles. These species cause electronic deficiency on Cu surfaces, which enhances the adsorption of the reactants.

SPP zeolite has been chosen as the support to accommodate the Cu/ZnO composite particles in the present study. SPP zeolite is available as ellipsoidal particles in sizes of several hundred nanometers. The particles have a "house of cards" structure built up of ∼2 nm thick nanosheets of the MFI-type zeolite. The nanosheets penetrate each other perpendicularly, forming chambers with $2-8$ nm edges.²⁵⁻²⁷ There are several works demonstrating the role of the SPP zeolite as catalyst compositions or catalyst supports. Sn- and Sn/B-containing SPP zeolites were studied as catalysts for the conversions of sugar molecules.^{28,29} Phosphorus-loaded SPP was active in the tetrahydrofuran conversion to butadiene.³⁰ As a support for metal catalysts, SPP zeolite was found to stabilize sub-nanometer Rh and Rh–Ru clusters and was tested in the hydrogenation of various chemicals by ammonia borane.³¹ Herein, we used the pure-silica version of SPP to eliminate the contribution of acid sites and keep the focus of the study on the Cu/ZnO species. Over a Cu/ZnO-SPP-zeolite composite, the formation and evolution of the adsorbed intermediates were followed using in situ FTIR spectroscopy. Also, quasi-in situ XPS was used to confirm the surface electronic deficiency of Cu particles.

Experimental

Materials

SPP zeolite was synthesized according a procedure adapted from ref. 25 Cu and Zn were loaded on the calcined SPP

zeolite through incipient wetness impregnation using aqueous solutions of $Cu(NO₃)₂·3H₂O$ and $Zn(NO₃)₂·6H₂O$ at $Cu: Zn = 7:3$ (molar ratio). Ethylenediamine (3.0 mol eq. referring to the total amount of the metals) was added in the impregnation solutions as an agent to aid the metal dispersions. The metal loadings were 25.56 wt% CuO and 11.21 wt% ZnO, calculated on the oxide bases (CuZn-SPP-E in Table 1). A reference material CuZn-SPP was prepared through the same procedure but without ethylenediamine in the impregnation solution. Another reference, a Cu/ZnO/ Al_2O_3 catalyst of the composition $(6.3/2.7/1.0 \text{ wt})$, was prepared using the conventional co-precipitation method (Table 1). The synthetic procedure and basic properties of the pure-silica SPP zeolite are elaborated in the ESI† Section 1, Fig. S1 and S2. **Paper** Reading continuous continuous articles. The minimizary on 21 september 2024. The minimizary and $\frac{1}{2}$ september 2024. The minimizary articles are interesting to the simulation of CaPbO₂)-21.9 and 2000-211,

Characterization

Powder X-ray diffraction was performed on a Rigaku SmartLab diffractometer using Cu Kα radiation at 40 kV and 150 mA operating in the continuous scan mode in theta– theta geometry at $2\theta = 5-80^{\circ}$ for phase identification.

SEM images were taken on a Hitachi S-4800 scanning electron microscope equipped with a cold-field emission gun operating at 5 kV. The powder samples were dusted on carbon sheets and inspected without coating.

The TEM, STEM images, and corresponding EDS were taken on a JEOL JEM-F200 electron microscope. The samples were suspended in ethanol and dispersed onto ultrathin carbon films supported on 200 mesh Au grids.

FTIR spectra were recorded using a Bruker Vertex 70 V spectrometer at a spectral resolution of 4 cm⁻¹. The sample chamber and the optics chamber were evacuated to $\langle 1 \text{ hPa.} \rangle$ The in situ FTIR studies were performed on self-sustained pellets of a density 15 mg cm⁻², which were enclosed in a gas-tight and heated cell with $CaF₂$ windows. For probing the surfaces with $CO₂$ or the mixture of $CO₂$ and $H₂$, the sample was reduced at 400 °C in a 4% H_2/Ar flow at first. After cooling down to 150 °C, the background spectra were recorded. Then, a flow of $CO₂$ or $CO₂/3H₂$ was introduced into the cell for 30 min at 30 mL min−¹ , along with spectral recording in 1 min intervals.

Quasi-in situ XPS (X-ray Photoelectron Spectroscopy) experiments were carried out on an ESCALAB 250Xi spectrometer (Thermo Fisher Scientific) equipped with a monochromatic Al K α radiation source (E = 1486.6 eV). A heated chamber with gas inlets/outlets was used for the activation treatments. Samples were treated in 10% H_2/Ar

flow at 350 °C for 2 h, then in the reactive feed flow (CO_2/H_2) = 1/3) for 2 h at different temperatures between 180 and 280 °C. Afterwards, the chamber was evacuated and the sample was analyzed.

N2 adsorption and desorption data were collected on a Quantachrome Autosorb iQ3 at 79 K. Samples were pretreated under vacuum at 350 °C for 10 h.

 H_2 -TPR (temperature-programmed reduction by H_2) experiments were carried out in a flow equipment with a thermal conductivity detector. 100 mg samples were pretreated in Ar at 350 °C for 2 h and cooled down to room temperature. The temperature was ramped at 10 $\mathrm{^{\circ}C}$ min⁻¹ to 800 °C in 5% H_2/Ar flow.

To carry out $N₂O$ titration, 100 mg reduced sample was exposed to 20% N₂O/Ar at 60 °C for 1 h. After Ar purging, the surface-oxidized sample was tested with H_2 -TPR again. The dispersion rate, defined as the portion of surface Cu atoms against the total atoms in the particle, was calculated as

$$
D_{\text{Cu}}(\text{H}_2 \text{TPR}) = \frac{10^{-6} \times n_{\text{H}_2} \text{ consumption} \times 5 \times M_{\text{Cu}}}{\omega_{\text{Cu}}}.
$$

where M_{Cu} is the molar mass of copper (63.55 g mol⁻¹) and ω_{Cu} is the Cu content determined by ICP-MS.

Catalytic test

Catalytic tests were carried out using a fixed-bed plug-flow microreactor with Φ = 0.4 mm and L = 50 mm (V_{bed} = 0.6 mL with 0.1 g catalyst diluted in quartz, grain sizes 60–100 mesh). The feed was $CO_2/H_2 = 1:3$ (3 MPa) at 30 mL min⁻¹, GHSV = 3000 h⁻¹, or WHSV_{CO₂} = 9.3 g h⁻¹ g_{cat}^{-1} . The activity was tested in the range of 180–300 °C for 3–5 hours at each temperature with 20 °C intervals. The outlet gas composition was analyzed by an online gas chromatograph (GC) equipped with an HP Plot/Q column connected to a thermal conductivity detector (TCD).

CO2 conversion, methanol yield, selectivity, and space time yield of methanol were calculated on carbon bases using the equations below, where N is the mol fraction of the respective component in the reaction gas flow and M is the mol mass in [g mol⁻¹]. STY in the dimension [g h⁻¹ g_{cat} ⁻¹] was calculated using $d_{\text{cat/bed}} = 0.1 \text{ g}/0.6 \text{ mL}$. The turn-over frequency of $CO₂$ and $CH₃OH$ formation rate were normalized to time and Cu weight.

$$
X_{\rm CO_2} = \frac{N_{\rm CH_3OH} + N_{\rm CO}}{N_{\rm CO_2} + N_{\rm CH_3OH} + N_{\rm CO}} \times 100\%
$$

$$
Y_{\text{CH}_3\text{OH}} = \frac{N_{\text{CH}_3\text{OH}}}{N_{\text{CO}_2} + N_{\text{CH}_3\text{OH}} + N_{\text{CO}}} \times 100\%
$$

$$
S_{\text{CH}_3\text{OH}} = \frac{N_{\text{CH}_3\text{OH}}}{N_{\text{CH}_3\text{OH}} + N_{\text{CO}}} \times 100\%
$$

$$
STY_{\text{CH}_3\text{OH}} = GHSV \times \frac{0.25}{1000 \times 22.4} \times Y_{\text{CH}_3\text{OH}} \times \frac{M_{\text{CH}_3\text{OH}}}{d_{\text{cat/bed}}}
$$

Results and discussion

Basic properties of the catalyst

The catalyst under study is a SPP zeolite loaded with Cu and Zn components. Fig. 1 shows the characterization of the catalyst CuZn-SPP-E prepared by impregnating metal nitrite precursors with the aid of ethylenediamine as a dispersion agent,³² in comparison with the reference material CuZn-SPP, prepared using the same precursors but without the dispersing agent. The metal loading amounts achieved 25.6 and 11.2 wt% for CuO and ZnO, respectively, in CuZn-SPP-E (Table 1). Ethylenediamine played a role in regulating the slow releases of metal ions during the preparation process, aiming at a uniform deposition of smaller metal oxide particles throughout the zeolite. In XRD, only weak and broad diffraction peaks for CuO and none were observed for ZnO were observed. Further, SEM observed that CuZn-SPP-E had the same morphology as the starting SPP zeolite, i.e., ellipsoidal particles with the long axis of about 100 nm, and the particles were made of intersecting sheets of ca. 2 nm thicknesses. The particles had clean surfaces, without observable foreign particles attached. The TEM images show 2–8 nm metal oxide particles randomly across the entire SPP zeolite particles. The N_2 adsorption isotherm shows that the metal oxide particles occupied a portion of the mesopores and partially blocked the access to the micropores (Table 2). H_2 -TPR and N_2O-H_2 titration experiments could determine a RSC Applied Interfaces

Case 21 sign at the reaction content and the sample of the anti-published on a

"Ca) Most 2 in different interpretation showers collected on a

"Ca) syntaple and description data one collected on a

Fig. 1 Physical properties of CuZn-SPP-E, compared with CuZn-SPP: (A) powder XRD patterns, (B) N_2 adsorption isotherms; SEM images (C for CuZn-SPP-E and F for CuZn-SPP); TEM images in the bright and dark fields (D and E for CuZn-SPP-E, G and H for CuZn-SPP).

value of Cu dispersion of 24.0%, defined as the portion of surface Cu atoms in the entire Cu particles in the reduced state.

Without ethylenediamine, less uniform deposition of metal particles with broad size distribution was obtained. In the reference CuZn-SPP material, a separation of the metal particles entrapped in the zeolite and those remaining at the external surface of the zeolite was observed at lower loadings, 18.3 wt% for CuO and 8.1 wt% for ZnO. XRD showed sharper and higher diffraction peaks for CuO. The SEM images show the crystallites attached to the external surfaces of the SPP zeolite particles.

TEM images displayed both smaller particles inside the zeolite and larger particles outside. Consistently, N_2 adsorption showed that less mesopore volumes were occupied, while more micropores remained accessible. The Cu dispersion rate was 7.1%.

Catalytic performance

Fig. 2 shows the steady state (3–5 hours of time-on-stream) $CO₂$ conversion, CH₃OH and CO selectivity (carbon-based), CO2 conversion rate and CH3OH formation rate per unit Cu for the CuZn-SPP-E material at the reaction temperatures of 180–300 °C, in comparison with CuZn-SPP and the coprecipitated Cu/ZnO/Al₂O₃ material of the composition (6.3) 2.7/1.0 wt), which is typical for commercial catalysts.³³ CH₃-

Fig. 2 Catalytic performances of CuZn-SPP-E, compared with CuZn-SPP and Cu/ZnO/Al2O3: CO2 conversion, χ_{CO_2} ; selectivity for CH3OH, S_{CH_3OH} and for CO, S_{CO} ; turn-over-frequency of CO₂ per unit Cu, $\mathsf{TOF}_{\mathsf{CO}_2}$; and the formation rate of $\mathsf{CH}_3\mathsf{OH}$ per unit Cu. The test conditions were feeding $CO_2/H_2 = 1/3$ at P = 3 MPa and WHSV_{CO₂} = 9.3 g h $^{-1}$ g $_{\rm cat}$ $^{-1}$.

OH, CO and $H₂O$ were the observed products at the tested conditions. Heavier compounds such as C_2H_5OH and hydrocarbons were absent.

Over CuZn-SPP-E, $CO₂$ conversion started with 2.4% at 180 °C and gradually grew to 26% until 300 °C. The CuZn-SPP catalyst, i.e., the material with a similar amount of metal loadings but at a lower dispersion rate, showed lower $CO₂$ conversion in the same temperature range. The larger particles on the external surfaces of the zeolite had lower activities. CuZn-SPP exhibited a sufficient activity only at higher temperatures, where the productivity of methanol is not satisfactory. Thus, the uniform distribution of smaller metal particles inside the zeolite in CuZn-SPP-E was beneficial.

Compared to $Cu/ZnO/Al₂O₃$, both SPP-supported catalysts were weak in terms of $CO₂$ conversion and $CH₃OH$ yield because of the lower loadings of Cu and Zn components. However, the performance of CuZn-SPP-E regarding the $CO₂$ conversion and CH3OH selectivity was already close to that of $Cu/ZnO/Al₂O₃$, with less than a half of the active components. When we consider the efficiency of unit Cu loadings, both $CO₂$ turnover frequency and $CH₃OH$ formation rate on unit Cu are significantly higher for the CuZn-SPP-E sample than those for $Cu/ZnO/Al₂O₃$. The SPP-supported, highly dispersed and smaller metal particles exhibited higher activity than Cu/ ZnO/Al_2O_3 with respect to the efficiency of the Cu active component by providing a higher number of surface sites. **Paper**
 **Open Access Article areas and some volumes of the SFP accide and the SFP-useported CoOZinO centers

Martink. In the strain of the strain of**

Electron deficiency transferred from ZnO to Cu as detected by quasi-in situ XPS

For the Cu/ZnO/Al₂O₃ catalyst, it is known that ZnO interacts with the metallic Cu particles as a bulk support and as surface overlayers. Moreover, some Zn atoms alloy in the Cu particles. In both cases, Zn species causes positive electronic charges to the metallic Cu particles, enhancing the interaction with $CO₂$ by polarizing the C=O bonds.19,20,23,33,34 It can be envisaged that ZnO and Zn play similar roles in the CuZn-SPP-E material. However, due to the high dispersion degrees and the SPP zeolite's unique nanostructure, our TEM inspection could not disclose more structural details of Zn species. XRD could only deduce that bulk crystalline ZnO or other Zn compounds were absent. ZnO was not supposed to be reduced in the TPR conditions. If some ZnO underwent reduction and alloyed with Cu, the small portion was also below TPR's detection ability.

Therefore, quasi-in situ XPS experiments were carried out to analyze the valences of Cu and Zn species under the

Fig. 3 Quasi-in situ XPS spectra of CuZn-SPP-E at the calcined, reduced, and after reaction testing states at the given temperatures (180–280 °C): Cu 2p (A), Cu LMM (B), Zn 2p (C), Zn LMM (D).

reaction conditions. Fig. 3 shows the X-ray photoelectron and X-ray excited Auger electron spectra of CuZn-SPP-E for the calcined, reduced, and after reaction testing states at various temperatures. In the Cu 2p spectra of the calcined sample (Fig. 3A), besides the shift splitting of Cu $2p_{1/2}$ and Cu $2p_{3/2}$, strong Cu^{2+} satellites indicated that Cu was present as CuO. The Cu LMM curve had an Auger peak at 915.5 eV (Fig. 3B), which also corresponded to CuO. After the reduction in H_2 , CuO was converted completely to metallic $Cu⁰$, with the Cu 2p_{3/2} peak at 932.4 eV, Cu 2p_{1/2} at 952.1 eV, Δ = 19.7 eV, and the Cu LMM peak at 918.2 eV .^{35,36} The spectra remained unchanged after the reaction tests from 180 to 280 °C. The expected electron deficiency is neither obvious for the reduced material nor for the samples that experienced the reaction conditions in the XPS spectra.

The rather large splitting of Zn $2p_{3/2}$ (1022.1 eV) and Zn $2p_{1/2}$ (1045.5 eV) of $\Delta = 22.4$ eV implies that Zn was present as ZnO in the calcined CuZn-SPP-E sample (Fig. 3C). In the Zn LMM spectra, the Auger peak corresponding to Zn^{2+} appeared at 986.4 eV (Fig. 3D), while the $\text{Zn}^{\delta+}$ (δ < 2) peak at 989.2 eV also had a non-negligible intensity. Here, the O vacancies caused an electron deficiency in the ZnO species. After the reduction and the catalytic tests, the 2p spectra moved to slightly higher binding energies (1022.6 and 1046.0 eV) while the Auger binding energies became lower (985.9 eV), indicating that Zn was in a more oxidized state after the reduction and during the reaction, i.e., the oxygen vacancy was partly filled by taking over the oxygen from CuO and/or electron from Cu. Also, it was plausible to deduce that the electron deficiency was transferred to the Cu particles, thus strengthening the adsorption and polarization of $C=O$ bonds under the reaction conditions.

The quasi-in situ XPS spectra of the CuZn-SPP catalysts are provided in the ESI† in Fig. S3. Despite different spectroscopic intensities due to the different amounts of exposed surface sites, they supported the same hypothesis that the electron deficiency at the O vacancy of ZnO transferred to Cu particles after the reduction and during the catalytic reaction.

In the XPS spectra for O 1s (Fig. S4 in the ESI†), only one shift at 532.8 eV was observed for the freshly prepared CuZn-SPP-E sample. It covers the oxygen bonds in the zeolite framework as well as the ones in CuO and $ZnO.³⁷$ After the exposure to $H₂$, this peak shifted to a higher binding energy at 533.3 eV due to the reduction of CuO to Cu 0 . The same procedure was observed for CuZn-SPP. Red shifts of the binding energy occurred when the materials were exposed to the reaction conditions, where binding and chemisorption of oxygen-containing reaction intermediates at the Cu surfaces, especially H₂O, were present. For CuZn-SPP-E, the red shift was about 0.2 eV, whereas it was 0.5 eV for CuZn-SPP. The catalyst with smaller and uniform metal particles favored smooth transitions and desorption of these intermediates. Unfortunately, no signal related to the charge exchange between Cu particles and the O vacancies in ZnO could be resolved. The contributions of the rather small amount of O vacancies to the shifts in the binding energy were insignificant. **Exampled interfaces** the computation and the electron conditions are the common and the electron conditions are the common and the electron common and the electron common and the electron common and the electron common a

In situ FTIR-recognizable reaction intermediates

Fig. 4 shows the in situ FTIR spectra of the reduced CuZn-SPP-E catalysts exposed to flowing CO_2 and then to $CO_2/3H_2$ at 150 °C. Several reaction intermediate species already appeared upon the initial adsorption of $CO₂$. The peaks at 2075 cm⁻¹ and 2060 cm⁻¹ corresponded to the stretching vibration of carbonyl that bonded to Cu metal surfaces (Cu– $C=O$).^{24,38,39} The appearance of two distinctive carbonyl bands for Cu implied that the charge distribution on the metal surfaces was not even. A weaker $d-\pi$ feedback along the bond Cu–C \equiv O caused the band at a higher frequency and indicated electron-deficient spots.⁴⁰ One reason for the electron deficiency was the surface oxidation by $CO₂$. Additional electron deficiency was caused by the transformation from the oxygen vacancy of ZnO, in accordance with quasi-in situ XPS. One more carbonyl peak at 2130 cm^{-1} was due to the surface carbonyl on ZnO.^{24,41} Further carbonyl stretching was observed at 1900 cm⁻¹, which

Fig. 4 In situ FTIR spectra of the reduced CuZn-SPP-E catalyst exposed to flowing CO_2 (A) and then to CO_2+3H_2 (B) at 150 °C.

is attributed to the bridged C= O on Cu or ZnO surfaces.^{42,43} Bands belonging to surface adsorbed carbonate were observed, which were due to the asymmetric bending vibration at 1520 cm^{-1} and symmetric bending at 1380 cm−¹ . 42,44,45

On co-feeding 3 mol eq. H_2 with CO_2 , both the surfaceadsorbed carbonyls and carbonates were consumed rapidly. Two new bands appeared: the peak at 1590 $\mathrm{cm}^{-1},$ which was due to the O–C–O bending vibration of mono-dentated formate adsorbed on Cu surfaces, and at 1346 cm^{-1} due to the bi-dentate formate on Cu.^{38,39,42,46–48} The peak intensity changes approached a steady state within approximately 5 min.

Physisorbed water was built-up during the adsorption of $CO₂$, together with the formation of surface carbonyls and formates, which is recognized by the –O–H stretching at 1630 cm−¹ . 39,46,49 The initial source of hydrogen must be the layer of chemisorbed H atoms on the reduced Cu surfaces. The overall intensities of the adsorbed water were not high and became even lower when the reactions proceeded. The reaction intermediates expelled a portion of the adsorbed water.

Fig. 5 shows the in situ FTIR spectra of CuZn-SPP at the same conditions. CuZn-SPP, which had larger Cu particles at the external surfaces of SPP zeolite, accumulated more bridged carbonyl and more physisorbed water when exposed to $CO₂$. Thus, both signals stayed during the reactions. Bridged carbonyl is less reactive than the linearly adsorbed one. This explains that the material performed less efficiently, especially at lower reaction temperatures.

The in situ FTIR spectra of the reduced catalysts directly exposed to the reaction feeds (without the pre-adsorption of $CO₂$) were also recorded and are illustrated as the ESI[†] in Fig. S5 and S6. Without the initial accumulation of the first carbonyls and carbonates out of $CO₂$, the reactions still approached the same steady states within ca. 5 minutes.

Compared to the 1 nm Cu particles entrapped in the grain boundaries of nanosilicalite-1 reported before, 17 less intermediate species were observable on CuZn-SPP-E and CuZn-SPP, specifically, HCOOH* and HCO* were absent. Fig. 6 summarizes the expected reaction intermediates when the reactions proceed through both the formate route and the RWGS route.19,20 The red circles indicate the reaction

Fig. 6 The expected reaction intermediates for $CO₂$ hydrogenation to methanol, and the ones recognized by in situ FTIR over 1 nm Cu particles entrapped in silicalite-1 (red circles),¹⁷ and 2-8 nm Cu/ZnO in SPP zeolite (blue circle).

intermediates detected by in situ FTIR over the 1 nm Cu particles entrapped in silicalite- $1¹⁷$ The blue circles indicate the ones recognized in the present study over 2–8 nm Cu/ ZnO in SPP zeolite. The intermediates related to the formateroute were preferentially consumed than the carbonyls over the smaller Cu particles. But the current study on ZnO modified and larger Cu particles would not allow to distinguish both. The absence of COOH* and HCOO* and subsequent intermediates and the fast consumption of carbonyls and formates implies that these reaction intermediates were very rapidly converted to the products. The reactions proceed faster on the ZnO-modified and zeolite enclosed 2–8 nm Cu particles. **Paper**
 Example 10 simulated on 21 september 2024. Determines a recession of the relationship is article in a symmetric bend on 21 september 2022. The commons are determined by the simulated articles. The commons are c

The in situ XPS and FTIR results together support the conclusion that the transfer of electron deficiency from the ZnO oxygen vacancy to the Cu surfaces promotes the activation of $CO₂$. Thus, it is interesting to study how the ZnO species affect the small Cu nanoparticles entrapped in zeolites. Here, as a first attempt, Fig. 7 illustrates the TEM images and EDX elemental mapping of Si, O, Cu, and Zn for CuZn-SPP-E, which showed that the distribution area of Cu and Zn elements overlapped each other rather than that of the individual element crowded in certain spots. In the future, the structural relationship of Cu clusters and ZnO species could be characterized in detail through further experimental and theoretical studies.

Fig. 5 In situ FTIR spectra of the reduced CuZn-SPP catalyst exposed to flowing $CO₂$ (A) and then to $CO₂+3H₂$ (B) at 150 °C.

Fig. 7 TEM images and elemental mapping of Si, O, Cu, and Zn for CuZn-SPP-E.

It is also expected that the confinement in the mesopores of the SPP zeolite would stabilize the metal particles against sintering. We begin to investigate this point by cycling the catalytic test experiments. Fig. 8 shows the $CO₂$ conversion and CH3OH selectivity over the CuZn-SPP-E catalyst in 5 test cycles for 5 hours at each temperature step and total 175 hours in the whole experiment. The results show that both conversion and selectivity deteriorated slightly in the 2nd and 3rd cycles but were stabilized in the subsequent cycles. Taking the values at 240 °C, the $CO₂$ conversion stabilized from 17% to about 13% and the CH₃OH selectivity from 36% to 30%. Considering that the catalyst was exposed to harsh temperature conditions of up to 300 °C in each cycle, the deterioration in performance can be considered not severe. The potential of the SPP zeolite to stabilize smaller metal particles by trapping them in the mesopores is thus confirmed. In addition, the stability of the catalyst should be compared with that of the commercial Cu/ZnO/Al₂O₃ catalyst by longer and more extensive tests, e.g., at a temperature of about 230 °C for at least 1000 h, as described by Schlögl et al. in a benchmark study. 33 The spent catalyst in various stages of deactivation will be thoroughly characterized in order to develop further means of preventing sintering and other types of deterioration. **Excelled interfaces**
 Excellent access Article and the proposed on 21 september 2024. The common access are computed to the common access Article is licensed under the set of the set of the set of the set of the set of

Conclusions

The Cu/ZnO/SPP-zeolite composite, with CuO particle sizes in the range of 2–8 nm that are uniformly embedded within the mesopores of the SPP zeolite having loading amounts up to 25.6 wt% for CuO and 11.2 wt% for ZnO, acts as an active catalyst in $CO₂$ hydrogenation to $CH₃OH$ and CO. It performs better than the Cu/ZnO/Al₂O₃ catalyst in terms of $CO₂$ turnover frequency and methanol formation rate per unit Cu. But the overall performance of the zeolite-supported materials is still not able to match that of the $Cu/ZnO/Al₂O₃$ catalyst because of the low metal loadings.

Reduced metal particle size accelerated the reaction speeds. Quasi-in situ XPS and in situ FTIR experiments determined that the electronic deficiency due to the oxygen vacancy in ZnO can be transferred to Cu particles during the reactions and promote the interaction with CO₂. CuZn-SPP-E can maintain a constant carbonate coverage and low water adsorption during the catalytic reaction. Intermediates related with the hydrogenation processes, such as adsorbed carbonyl and formate species, are turned over very rapidly. The structures of ZnO and its relationship with Cu particles and SPP zeolite have not been characterized yet and will be the focus of future studies. It is also discovered in the in situ experiments that larger Cu/ZnO particles on SPP zeolite are prone to stronger water adsorption.

Detailed investigations into the structure and role of the ZnO promoter as well as longer and larger stability tests are being carried out.

Data availability

The data supporting this article have been included as part of the ESI,† including the preparation and characterization of the starting SPP zeolite, and additional in situ FTIR and quasi-in situ XPS spectra recorded in various reactive flows. Further details are available from the authors upon request.

Author contributions

X. Liu: investigation. G. Fu: conceptualization, methodology, supervision, investigation. Q. Lang, R. Ding, Q. Guo, K. Liang, S. Gao: investigation. X. Yang: methodology, investigation, writing – original draft. B. Yu: supervision.

Conflicts of interest

There are no conflicts to declare.

Acknowledgements

Fundings were provided by Shandong Energy Institute (SEI S202107), and Natural Science Foundation of Shandong Province, China (ZR2022MB053, ZR2022QB216).

References

- 1 J. Zhong, X. Yang, Z. Wu, B. Liang, Y. Huang and T. Zhang, Chem. Soc. Rev., 2020, 49, 1385–1413.
- 2 George Olah CO₂ to Renewable Methanol Plant, Reykjanes, Iceland, <https://www.carbonrecycling.is/>.
- 3 P. Gao, L. Zhang, S. Li, Z. Zhou and Y. Sun, ACS Cent. Sci., 2020, 6, 1657–1670.
- 4 P. Sharma, J. Sebastian, S. Ghosh, D. Creaser and L. Olsson, Catal. Sci. Technol., 2021, 11, 1665–1697.
- 5 P. Gao, S. Li, X. Bu, S. Dang, Z. Liu, H. Wang, L. Zhong, M. Qiu, C. Yang, J. Cai, W. Wei and Y. Sun, Nat. Chem., 2017, 9, 1019–1024.
- 6 S. Dang, B. Qin, Y. Yang, H. Wang, J. Cai, Y. Han, S. Li, P. Gao and Y. Sun, Sci. Adv., 2020, 6, eaaz2060.
- 7 J. Wang, T. Wang, Y. Xi, G. Gao, P. Sun and F. Li, Angew. Chem., Int. Ed., 2023, e202311335.
- 8 L. Liu and A. Corma, Chem. Rev., 2018, 118, 4981–5079.
- 9 C. R. Henry, C. Chapon, S. Giorgio and C. Goyhenex, in Chemisorption and Reactivity on Supported Clusters and Thin

Films: Towards an Understanding of Microscopic Processes in Catalysis, ed. R. M. Lambert and G. Pacchioni, Springer Netherlands, Dordrecht, 1997, pp. 117–152, DOI: [10.1007/](https://doi.org/10.1007/978-94-015-8911-6_5) [978-94-015-8911-6_5](https://doi.org/10.1007/978-94-015-8911-6_5).

- 10 Y. Wang, C. Wang, L. Wang, L. Wang and F.-S. Xiao, Acc. Chem. Res., 2021, 54, 2579–2590.
- 11 Y. Chai, W. Shang, W. Li, G. Wu, W. Dai, N. Guan and L. Li, Adv. Sci., 2019, 6, 1900299.
- 12 Q. Zhang, S. Gao and J. Yu, Chem. Rev., 2023, 123, 6039–6106.
- 13 N. Kosinov, C. Liu, E. J. M. Hensen and E. A. Pidko, Chem. Mater., 2018, 30, 3177–3198.
- 14 E. B. Clatworthy, S. V. Konnov, F. Dubray, N. Nesterenko, J.-P. Gilson and S. Mintova, Angew. Chem., Int. Ed., 2020, 59, 19414–19432.
- 15 W.-G. Cui, Y.-T. Li, L. Yu, H. Zhang and T.-L. Hu, ACS Appl. Mater. Interfaces, 2021, 13, 18693–18703.
- 16 L. Ding, T. Shi, J. Gu, Y. Cui, Z. Zhang, C. Yang, T. Chen, M. Lin, P. Wang, N. Xue, L. Peng, X. Guo, Y. Zhu, Z. Chen and W. Ding, Chem, 2020, 6, 2673–2689.
- 17 R. Ding, G. Fu, S. Wang, Y. Yang, Q. Lang, H. Zhao, X. Yang and V. Valtchev, Catalysts, 2022, 12, 1296.
- 18 X. Yang, E. Dib, Q. Lang, H. Guo, G. Fu, J. Wang, Q. Yi, H. Zhao and V. Valtchev, Microporous Mesoporous Mater., 2022, 329, 111537.
- 19 L. C. Grabow and M. Mavrikakis, ACS Catal., 2011, 1, 365–384.
- 20 M. Behrens, F. Studt, I. Kasatkin, S. Kühl, M. Hävecker, F. Abild-Pedersen, S. Zander, F. Girgsdies, P. Kurr, B.-L. Kniep, M. Tovar, R. W. Fischer, J. K. Nørskov and R. Schlögl, Science, 2012, 336, 893–897.
- 21 P. L. Hansen, J. B. Wagner, S. Helveg, J. R. Rostrup-Nielsen, B. S. Clausen and H. Topsøe, Science, 2002, 295, 2053–2055.
- 22 T. Lunkenbein, J. Schumann, M. Behrens, R. Schlögl and M. G. Willinger, Angew. Chem., Int. Ed., 2015, 54, 4544–4548.
- 23 T. Lunkenbein, F. Girgsdies, T. Kandemir, N. Thomas, M. Behrens, R. Schlögl and E. Frei, Angew. Chem., Int. Ed., 2016, 55, 12708–12712.
- 24 J. Schumann, J. Kröhnert, E. Frei, R. Schlögl and A. Trunschke, Top. Catal., 2017, 60, 1735–1743.
- 25 X. Zhang, D. Liu, D. Xu, S. Asahina, K. A. Cychosz, K. V. Agrawal, Y. Al Wahedi, A. Bhan, S. Al Hashimi, O. Terasaki, M. Thommes and M. Tsapatsis, Science, 2012, 336, 1684–1687.
- 26 W. Chaikittisilp, Y. Suzuki, R. R. Mukti, T. Suzuki, K. Sugita, K. Itabashi, A. Shimojima and T. Okubo, Angew. Chem., Int. Ed., 2013, 52, 3355–3359.
- 27 R. Jain, A. Chawla, N. Linares, J. García Martínez and J. D. Rimer, Adv. Mater., 2021, 33, 2100897.
- 28 T. R. Josephson, R. F. DeJaco, S. Pahari, L. Ren, Q. Guo, M. Tsapatsis, J. I. Siepmann, D. G. Vlachos and S. Caratzoulas, ACS Catal., 2018, 8, 9056–9065.
- 29 H. Wu, W. Huang, J. Zhang, T. Du, J. Wang, Z. Xu, R. Xu, C. Meng, X. Guo, L. Ren and M. Tsapatsis, Microporous Mesoporous Mater., 2022, 341, 112068.
- 30 E. Ruiz-Zamora, J. R. De la Rosa, C. S. Maldonado, C. J. Lucio-Ortiz, D. A. D. H. D. Río, M. A. Garza-Navarro, L. Sandoval-Rangel, F. J. Morales-Leal and S. Wi, Appl. Catal., A, 2022, 640, 118648.
- 31 N. Wang, Q. Sun, T. Zhang, A. Mayoral, L. Li, X. Zhou, J. Xu, P. Zhang and J. Yu, J. Am. Chem. Soc., 2021, 143, 6905–6914.
- 32 C. Dong, Y. Li, D. Cheng, M. Zhang, J. Liu, Y.-G. Wang, D. Xiao and D. Ma, ACS Catal., 2020, 10, 11011–11045.
- 33 H. Ruland, H. Song, D. Laudenschleger, S. Stürmer, S. Schmidt, J. He, K. Kähler, M. Muhler and R. Schlögl, ChemCatChem, 2020, 12, 3216–3222.
- 34 S. Fujita, M. Usui, H. Ito and N. Takezawa, J. Catal., 1995, 157, 403–413.
- 35 G. Moretti, Surf. Sci., 2013, 618, 3–11.
- 36 N. J. Divins, D. Kordus, J. Timoshenko, I. Sinev, I. Zegkinoglou, A. Bergmann, S. W. Chee, S. Widrinna, O. Karslıoğlu, H. Mistry, M. Lopez Luna, J. Q. Zhong, A. S. Hoffman, A. Boubnov, J. A. Boscoboinik, M. Heggen, R. E. Dunin-Borkowski, S. R. Bare and B. R. Cuenya, Nat. Commun., 2021, 12, 1435. **Paper** Receives Articles. Articles Artic
	- 37 S. Wang, K. Feng, D. Zhang, D. Yang, M. Xiao, C. Zhang, L. He, B. Yan, G. A. Ozin and W. Sun, Adv. Sci., 2022, 9, 2104972.
	- 38 F. C. Meunier, Catal. Today, 2023, 423, 113863.
	- 39 D. B. Clarke and A. T. Bell, J. Catal., 1995, 154, 314–328.
	- 40 E. Shaaban and G. Li, Commun. Chem., 2022, 5, 32.
	- 41 J. Hu, Y. Li, Y. Zhen, M. Chen and H. Wan, Chin. J. Catal., 2021, 42, 367–375.
	- 42 K. K. Bando, K. Sayama, H. Kusama, K. Okabe and H. Arakawa, Appl. Catal., A, 1997, 165, 391–409.
	- 43 C. Shao and M. Chen, J. Mol. Catal. A: Chem., 2001, 170, 245–249.
	- 44 J. Baltrusaitis, J. H. Jensen and V. H. Grassian, J. Phys. Chem. B, 2006, 110, 12005–12016.
	- 45 H. Bahruji, M. Bowker, G. Hutchings, N. Dimitratos, P. Wells, E. Gibson, W. Jones, C. Brookes, D. Morgan and G. Lalev, J. Catal., 2016, 343, 133–146.
	- 46 F. C. Meunier, I. Dansette, K. Eng and Y. Schuurman, Catalysts, 2022, 12, 793.
	- 47 F. C. Meunier, Angew. Chem., Int. Ed., 2011, 50, 4053–4054.
	- 48 J. Merel, M. Clausse and F. Meunier, Ind. Eng. Chem. Res., 2008, 47, 209–215.
	- 49 F. C. Meunier, R. Kdhir, N. Potrzebowska, N. Perret and M. Besson, Inorg. Chem., 2019, 58, 8021–8029.